

# MARTE Tutorial

An OMG standard:  
UML profile to develop Real-Time and Embedded systems


- **This presentation reuses and extends material prepared by the ProMARTE partners for the OMG RTESS PTF meeting in San Diego, on March 28<sup>th</sup> 2007**
- **This tutorial has been designed in the context of CORTESS project within the CARROLL research program**
  - <http://www.carroll-research.org/>
- **Following persons have contributed to this tutorial**
  - CEA LIST ( contact: [sebastien.gerard@cea.fr](mailto:sebastien.gerard@cea.fr))
    - Huascar Espinoza, Sébastien Gérard, Safouan Taha and Frédéric Thomas.
  - INRIA (contact: [Robert.De\\_simone@sophia.inria.fr](mailto:Robert.De_simone@sophia.inria.fr))
    - Charles André, Robert de Simone, Pierre Boulet
  - Thales TRT (contact: [Laurent.rioux@thalesgroup.com](mailto:Laurent.rioux@thalesgroup.com))
    - Madeleine Faugère, Laurent Rioux, Sebastien Demathieu

- Within next slides, we may shown models at different levels of abstraction. We will clarify each level through following pictograms


- For Domain View level



- For UML Profile View Level




- For User Model View Level



- **Part 1**
  - Introduction to MDD for RT/E systems & MARTE in a nutshell
- **Part 2**
  - Non-functional properties modeling
  - Outline of the Value Specification Language (VSL)
- **Part 3**
  - The timing model
- **Part 4**
  - A component model for RT/E
- **Part 5**
  - Platform modeling
- **Part 6**
  - Repetitive structure modeling
- **Part 7**
  - Model-based analysis for RT/E
- **Part 8**
  - MARTE and AADL
- **Part 9**
  - Conclusions

# Models in Traditional Engineering

- Probably as old as engineering



Extracted from B. Selic presentation during Summer School MDD  
For DRES 2004 (Brest, September 2004)

- Phil Bernstein, "A Vision for Management of Complex Systems".  
A model is a complex structure that represents a design artifact such as a relational schema, an interface definition (API), an XML schema, a semantic network, a UML model or a hypermedia document.
  - OMG, "UML Superstructure".  
A model captures a view of a physical system. It is an abstraction of the physical system, with a certain purpose. This purpose determines what is included in the model and what is relevant. Thus the model completely describes those aspects of the physical system that are relevant to the purpose of the model, at the appropriate level of detail.
  - OMG, "MDA Guide".  
A formal specification of the function, structure and/or behavior of an application or system.
  - Steve Mellor, et al., "UML Distilled"  
A model is a simplification of something so we can view, manipulate, and reason about it, and so help us understand the complexity inherent in the subject under study.
  - Anneke Kleppe, et. al. "MDA Explained"  
A model is a description of (part of) a system written in a well-defined language. A well-defined language is a language with well-defined form (syntax), and meaning (semantics), which is suitable for automated interpretation by a computer.
  - Chris Raistrick et al., "Model Driven Architecture with Executable UML"  
A formal representation of the function, behavior, and structure of the system we are considering, expressed in an unambiguous language.
  - J. Bézivin & O. Gerbé, "Towards a Precise Definition of the OMG/MDA Framework"  
A simplification of a system built with an intended goal in mind; The model should be able to answer questions in place of the actual system.
- **One definition**
- A reduced/abstract representation of some system that highlights the properties of interest from a given point of view.
  - The point of view defines concern and scope of the model.

- Map is based on a legend (explicit or implicit)
  - Here the map of bicycle roads of Seattle
- As a map, the legend is defined in a graphical language, it means also the legend is declared with a similar formalism.
- If the Map is a Model, the legend is the meta-model defining the subset of graphical language used to build the model
- The Legend is necessary to interpret the map.
- If the legend is not shown, this mean we refer to a standard legend and implicit.







The Legend

# A Model without its meta-model has no meaning


Candidates at the  
 Presidential election  
 In France in 2002

Percentage  
 Of town  
 infested of termites




From J. Bezivin / INRIA





System to model




Functional model

- For Functional viewpoint and its design

- **To deal with complexity of systems development**
  - Abstract a problem to focus on some particular points of interest  
→ improve understandability of a problem
  - Possible set of nearly independent views of a model
    - Separation of concerns (e.g. “Aspect Oriented Modeling”)
  - Iterative modeling may be expressed at different level of abstraction
- **To minimize development risks**
  - Through analysis and experimentation performed early in the design cycle
  - Enable to investigate and compare alternative solutions
- **To improve communication ...**
- **... to foster information sharing and reuse!**
  - A good model is better than a long speech !
- **To reduce development flaws**
  - Automatic model transformation is less error-prone than building a specific compiler

# Why: Provide Continuum in development process



- **Abstract**
  - Emphasize important aspects while removing irrelevant ones
- **Understandable**
  - Expressed in a form that is readily understood by observers
- **Accurate**
  - Faithfully represents the modeled system
- **Predictive**
  - Can be used to answer questions about the modeled system
- **Inexpensive**
  - Much cheaper to construct and study than the actual system

*To be useful, engineering models must satisfy all of these characteristics!*

(Extracted from B. Selic presentation during Summer School MDD For DRES 2004 (Brest, September 2004))


```
SC_MODULE(producer) {
  sc_outmaster<int> out1;
  sc_in<bool> start; // kick-start
  void generate_data () {
    for(int i =0; i <10; i++) {
      out1 =i ; //to invoke slave;
    }
  }
  SC_CTOR(producer) {
    SC_METHOD(generate_data);
    sensitive << start;
  }
};

SC_MODULE(top) { // container
  producer *A1;
  consumer *B1;
  sc_link_mp<int> link1;
  SC_CTOR(top) {
    A1 = new producer("A1");
    A1.out1(link1);
    B1 = new consumer("B1");
    B1.in1(link1);
  }
};
```

```
SC_MODULE(consumer) {
  sc_inslave<int> in1;
  int sum; // state variable
  void accumulate (){
    sum += in1;
    cout << "Sum = " << sum << endl;
  }
  SC_CTOR(consumer) {
    SC_SLAVE(accumulate, in1);
    sum = 0; // initialize
  }
};
```


**Can you spot the architecture?**

(Extracted from B. Selic presentation during Summer School MDD For DRES 2004 (Brest, September 2004))



**Can you spot the architecture?**

(Extracted from B. Selic presentation during Summer School MDD For DRES 2004 (Brest, September 2004))




- Models can be refined continuously until the specification is complete

(Extracted from B. Selic presentation during Summer School MDD For DRES 2004 (Brest, September 2004))

# Model-Driven Style of Development (MDD)

- An approach to develop systems and softwares in which the focus and primary artifacts of development are models (as opposed to programs)
- Based on two time-proven methods





- **Advantages of UML Profiles**
  - Reuse of language infrastructure (tools, specifications)
  - Require less language design skills
  - Allow for new (graphical) notation of extended stereotypes
  - A profile can define model viewpoints
    - E.g., UML activity diagram extended to specify multitask behavior
  
- **Disadvantage**
  - Constrained by UML metamodel


## ■ Profiles

- Define limited extensions to a reference metamodel with the purpose of adapting the metamodel to a specific platform or domain.
- Consists of stereotypes that extend the metamodel classes (metaclasses).

## ■ Stereotypes

- Define how a specific metaclass may be extended
- Provide additional semantics information, but only for:
  - Semantics restriction or clarification of existing concept
  - New features (but compatible with exiting one!)
- Ensure introduction of domain specific terminology
  - E.g., EAST-ADL2, a UML profile for automotive ECUs (<http://www.atesst.org>)
  - May define specific notation
    - E.g., new icons or shapes
- May have values that are usually referred to as tagged values

- Profile is a stereotyped package



- Applying a profile

- All extensions are then available for modeling



- If multiple profiles are applied:
  - Referenced MMs have to be identical...  
 ... and the model has also to refer the same MM.
  - Their constraint sets do not have to conflict
  - In case of naming conflict, use namespace notation
    - <ProfileName>::<StereotypeName>
    - e.g. «MyProfile1::name» & «MyProfile2::name»

Extracted from S.Gerard (ECRTS07)

- **A profile package may import external packages**

- "Normal" packages
  - e.g. external pkgs defining specific types for a profile



- "Profile" packages



- All imported elements may be used in pkgs applying the profile

Extracted from S.Gerard (ECRTS07)



■ **Stage 1** → **Description of MARTE domain models (Domain View)**

- Purpose: Formal description of the concepts required for MARTE
- Techniques: Meta-modeling











■ **Stage 2** → **Mapping of MARTE domain models towards UML2: (UML Representation)**

- Purpose: MARTE domain models design as a UML2 extensions
- Techniques: UML2 profile




Extracted from S.Gerard (ECRTS07)

# Example: Domain model → Profile → Usage




## ■ Stereotype definition





## ■ Required stereotype

- Extended meta-class may only be instantiated under its stereotyped form



## ■ Stereotype properties



## ■ Applying a stereotype





## ■ Applying several stereotypes





or



## ■ Specifying values of a stereotype



- Use name of stereotypes when possible confusion



Extracted from S.Gerard (ECRTS07)



Extracted from S.G erard (ECRTS07)



 Tool Support

 Time Analysis Support

- **SPT was the first OMG’s UML profile for Real-Time Systems:**
  - Support for **S**chedulability Analysis with RMA-type techniques
  - Support for **P**erformance Analysis with Queuing Theory and Petri Nets
  - A rich model for “metric” **T**ime and Time Mechanisms
- **Several improvements were required:**
  - Modeling HW and SW platforms, Logical Time, MoCCs, CBSE...
  - Alignment to UML2, QoS&FT, MDA,...
  - SPT constructs were considered too abstract and hard to apply
  - ...

Hence, a Request For Proposal for a new profile was issued.

## ■ Industrials

- Alcatel\*
- Lockheed Martin\*
- Thales\*
- France-Telecom

## ■ Tool vendors

- ARTISAN Software Tools\*
- International Business Machines\*
- Mentor Graphics Corporation\*
- Softeam\*
- Telelogic AB (I-Logix\*)
- Tri-Pacific Software
- France Telecom
- No Magic
- Mathworks

## ■ Academics


- Carleton University
- Commissariat à l'Énergie Atomique
- ESEO
- ENSIETA
- INRIA
- INSA from Lyon
- Software Engineering Institute (Carnegie Mellon University)
- Universidad de Cantabria

**Public website:**

[www.omgmarTE.org](http://www.omgmarTE.org)

\* Submitter to OMG UML Profile for MARTE RFP

- **Relationships with generic OMG standards**
  - Profile the UML2 superstructure meta-model
  - Replace UML Profile for SPT (Scheduling, Performance and Time)
  - Use OCL2 (Object Constraints Language)
  
- **Relationships with RT&E specific OMG standards**
  - Existing standards
    - The UML profile for Modeling QoS and FT Characteristics and Mechanisms
      - Addressed through MARTE NFP package (in a way detailed in the NFP presentation)
    - The UML profile for SoC (System On Chip)
      - More specific than MARTE purpose
    - The Real-Time CORBA profile
      - Real-Time CORBA based architecture can be annotated for analysis with Marte
    - The UML profile for Systems Engineering (SysML)
      - Specialization of SysML allocation concepts and reuse of flow-related concepts
      - Ongoing discussion to include VSL in next SysML version
      - Overlap of team members



Foundations for RT/E systems modeling and analysis:

- CoreElements
- NFPs
- Time
- Generic resource modeling
- Generic component modeling
- Allocation

Specialization of MARTE foundations for modeling purpose (specification, design, ...):

- RTE model of computation and communication
- Software resource modeling
- Hardware resource modeling

Specialization of foundations for annotating model for analysis purpose:

- Generic quantitative analysis
- Schedulability analysis
- Performance analysis