

Information technology – Object Management Group Unified Architecture Framework (UAF) Part 1: Domain Metamodel (DMM), 1.1

formal/22-04-03

This version has been formally published by ISO as the 2022 addition standard: ISO/IEC 19540-1.

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document are those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by the Object Management Group (OMG) and was adopted, under the PAS procedure, by Joint Technical Committee ISO/IEC JTC 1, Information technology, in parallel with its approval by national bodies of ISO and IEC.

This document is related to:

- ITU-T Recommendation X.902 (1995) | ISO/IEC 10746-2:1995, Information Technology – Open Distributed Processing – Reference Model: Foundations
- ITU-T Recommendation X.903 (1995) | ISO/IEC 10746-3:1995, Information Technology – Open Distributed Processing – Reference Model: Architecture
- ITU-T Recommendation X.920 (1997) | ISO/IEC 14750:1997, Information Technology – Open Distributed Processing – Interface Definition Language

Apart from this Foreword, the text of this document is identical with that for the OMG specification for Unified Architecture Framework (UAF) Part 1: Domain Metamodel (DMM), v1.1.

Introduction

The rapid growth of distributed processing has led to a need for a coordinating framework for this standardization and ITU-T Recommendations X.901-904 | ISO/IEC 10746, the Reference Model of Open Distributed Processing (RM-ODP) provides such a framework. It defines an architecture within which support of distribution, interoperability and portability can be integrated.

RM-ODP Part 2 (ISO/IEC 10746-2) defines the foundational concepts and modeling framework for describing distributed systems. The scopes and objectives of the RM-ODP Part 2 and the UML, while related, are not the same and, in a number of cases, the RM-ODP Part 2 and the UML specification use the same term for concepts which are related but not identical (e.g., interface). Nevertheless, a specification using the Part 2 modeling concepts can be expressed using UML with appropriate extensions (using stereotypes, tags, and constraints).

RM-ODP Part 3 (ISO/IEC 10746-3) specifies a generic architecture of open distributed systems, expressed using the foundational concepts and framework defined in Part 2. Given the relation between UML as a modeling language and Part 3 of the RM-ODP standard, it is easy to show that UML is suitable as a notation for the individual viewpoint specifications defined by the RM-ODP.

UAFP 1.1 supports the capability to:

- model architectures for a broad range of complex systems, which may include hardware, software, data, personnel, and facility elements;
- model consistent architectures for system-of-systems (SoS) down to lower levels of design and implementation;
- support the analysis, specification, design, and verification of complex systems; and
- improve the ability to exchange architecture information among related tools that are SysML based and tools that are based on other standards.

The intent of UAF is to provide a standard representation for describing enterprise architectures using a Model Based Systems Engineering (MBSE) approach.

Table of Contents

1	SCOPE	1
1.1	INTRODUCTION	1
1.2	UAF BACKGROUND	1
1.3	INTENDED USAGE	2
1.4	RELATED DOCUMENTS	2
2	CONFORMANCE	3
3	REFERENCES	4
3.1	NORMATIVE REFERENCES.....	4
3.2	OMG DOCUMENTS (NORMATIVE REFERENCES).....	4
3.3	OTHER NORMATIVE REFERENCES	4
3.4	INFORMATIVE REFERENCES.....	5
4	TERMS AND DEFINITIONS	6
5	SYMBOLS	7
6	ADDITIONAL INFORMATION	9
6.1	CHANGES TO ADOPTED OMG SPECIFICATIONS	9
6.2	LANGUAGE ARCHITECTURE	9
6.3	PHILOSOPHY.....	9
6.4	CORE PRINCIPLES	9
7	UAF GRID	11
7.1	DESCRIPTIONS OF DOMAINS AND MODEL KINDS	13
7.2	DOMAIN INTERRELATIONSHIPS.....	15
7.3	DOMAIN METAMODEL DIAGRAM LEGEND	15
8	DOMAIN METAMODEL DIAGRAMS	17
8.1	VIEW SPECIFICATIONS	17
8.1.1	<i>View Specifications::Metadata</i>	17
8.1.2	<i>View Specifications::Strategic</i>	18
8.1.3	<i>View Specifications::Operational</i>	26
8.1.4	<i>View Specifications::Services</i>	36
8.1.5	<i>View Specifications::Personnel</i>	45
8.1.6	<i>View Specifications::Resources</i>	60
8.1.7	<i>View Specifications::Security</i>	72
8.1.8	<i>View Specifications::Projects</i>	80
8.1.9	<i>View Specifications::Standards</i>	86
8.1.10	<i>View Specifications::Actual Resources</i>	89
8.1.11	<i>View Specifications::Dictionary</i>	92
8.1.12	<i>View Specifications::Summary & Overview</i>	93
8.1.13	<i>View Specifications::Requirements</i>	94
8.1.14	<i>View Specifications::Information</i>	95
8.1.15	<i>View Specifications::Parameters</i>	96
8.1.16	<i>View Specifications::Other</i>	99
9	DOMAIN METAMODEL (DMM) ELEMENTS	103

9.1	DOMAIN METAMODEL	103
9.1.1	<i>Domain MetaModel::Metadata</i>	103
9.1.2	<i>Domain MetaModel::Strategic</i>	117
9.1.3	<i>Domain MetaModel::Operational</i>	128
9.1.4	<i>Domain MetaModel::Services</i>	142
9.1.5	<i>Domain MetaModel::Personnel</i>	150
9.1.6	<i>Domain MetaModel::Resources</i>	157
9.1.7	<i>Domain MetaModel::Security</i>	175
9.1.8	<i>Domain MetaModel::Projects</i>	190
9.1.9	<i>Domain MetaModel::Standards</i>	197
9.1.10	<i>Domain MetaModel::Actual Resources</i>	199
9.1.11	<i>Domain MetaModel::Dictionary</i>	205
9.1.12	<i>Domain MetaModel::Summary & Overview</i>	207
9.1.13	<i>Domain MetaModel::Information</i>	211
9.1.14	<i>Domain MetaModel::Parameters</i>	212

TABLE OF FIGURES

Figure 7:1- UAF Grid.....	11
Figure 7:2 - Domain Interrelationships.....	15
Figure 7:3 - Legend of color codes for element types defined in UAF	16
Figure 8:1 - Strategic Taxonomy.....	19
Figure 8:2 - Strategic Structure.....	20
Figure 8:3 - Strategic Connectivity.....	21
Figure 8:4 - Strategic States.....	22
Figure 8:5 - Strategic Constraints	23
Figure 8:6 - Strategic Roadmap: Deployment	24
Figure 8:7 - Strategic Roadmap: Phasing	25
Figure 8:8 - Strategic Traceability	26
Figure 8:9 - Operational Taxonomy	27
Figure 8:10 - Operational Structure	28
Figure 8:11 - Operational Connectivity	29
Figure 8:12 - Operational Processes	30
Figure 8:13 - Operational Processes BPMN Semantics.....	32
Figure 8:14 - Operational States	33
Figure 8:15 - Operational Interaction Scenarios.....	34
Figure 8:16 - Operational Constraints	35
Figure 8:17 - Operational Traceability	36
Figure 8:18 - Services Taxonomy.....	37
Figure 8:19 - Services Structure	38
Figure 8:20 - Services Connectivity	39
Figure 8:21 - Services Processes	40
Figure 8:22 - Services Processes BPMN Semantics.....	41
Figure 8:23 - Services States	42
Figure 8:24 - Services Interaction Scenarios	43
Figure 8:25 - Services Constraints.....	44
Figure 8:26 - Services Roadmap.....	44
Figure 8:27 - Services Traceability.....	45
Figure 8:28 - Personnel Taxonomy	46
Figure 8:29 - Personnel Structure	47
Figure 8:30 - Personnel Connectivity	48
Figure 8:31 - Personnel Processes	49
Figure 8:32 - Personnel States	50
Figure 8:33 - Personnel Interaction Scenarios	51
Figure 8:34 - Personnel Constraints: Competence.....	53
Figure 8:35 - Personnel Constraints: Drivers.....	54
Figure 8:36 - Personnel Constraints: Performance	55
Figure 8:37 - Personnel Roadmap: Availability	57
Figure 8:38 - Personnel Roadmap: Evolution.....	58
Figure 8:39 - Personnel Roadmap: Forecast.....	59
Figure 8:40 - Personnel Traceability	60
Figure 8:41 - Resources Taxonomy.....	61
Figure 8:42 - Resources Structure	62
Figure 8:43 - Resources Connectivity	63
Figure 8:44 - Resources Processes	65
Figure 8:45 - Resources Processes BPMN Semantics.....	66
Figure 8:46 - Resources States	67
Figure 8:47 - Resources Interaction Scenarios	68
Figure 8:48 - Resources Constraints.....	69

Figure 8:49 - Resources Roadmap: Evolution	70
Figure 8:50 - Resources Roadmap: Forecast	71
Figure 8:51 - Resources Traceability	72
Figure 8:52 - Security Taxonomy	73
Figure 8:53 - Security Structure	74
Figure 8:54 - Security Connectivity	75
Figure 8:55 - Security Processes	77
Figure 8:56 - Security Constraints	78
Figure 8:57 - Security Traceability	80
Figure 8:58 - Project Taxonomy	81
Figure 8:59 - Project Structure	82
Figure 8:60 - Project Connectivity	83
Figure 8:61 - Project Processes	84
Figure 8:62 - Project Roadmap	85
Figure 8:63 - Project Traceability	86
Figure 8:64 - Standards Taxonomy	87
Figure 8:65 - Standards Structure	88
Figure 8:66 - Standards Roadmap	88
Figure 8:67 - Standards Traceability	89
Figure 8:68 - Actual Resources Structure	90
Figure 8:69 - Actual Resources Connectivity	91
Figure 8:70 - Actual Resources Traceability	92
Figure 8:71 - Dictionary	93
Figure 8:72 - Summary & Overview	94
Figure 8:73 - Requirements	95
Figure 8:74 - Information Model	96
Figure 8:75 - Parameters: Environment	97
Figure 8:76 - Parameters: Measurements	98
Figure 8:77 - BPMN	99
Figure 8:78 - IEPPV	100
Figure 8:79 - NIEM	101
Figure 9:1 - ArchitectureMetadata	103
Figure 9:2 - InteractionScenarioGeneralization	104
Figure 9:3 - Metadata	104
Figure 9:4 - ProcessGeneralization	105
Figure 9:5 - PropertySetGeneralization	105
Figure 9:6 - StateDescriptionGeneralization	106
Figure 9:7 - EnvironmentProperty	106
Figure 9:8 - Exchange	107
Figure 9:9 - ExchangeItem	107
Figure 9:10 - Resource	108
Figure 9:11 - ActivityPerformableUnderCondition	108
Figure 9:12 - IsCapableToPerform	109
Figure 9:13 - PerformsInContext	109
Figure 9:14 - Process	110
Figure 9:15 - Process	110
Figure 9:16 - ProcessEdge	111
Figure 9:17 - ProcessOperation	111
Figure 9:18 - ProcessParameter	112
Figure 9:19 - ProcessUsage	112
Figure 9:20 - StateDescription	113
Figure 9:21 - InteractionRole	113
Figure 9:22 - InteractionScenario	114
Figure 9:23 - Information	115
Figure 9:24 - Rule	115

Figure 9:25 - ArchitecturalReference	116
Figure 9:26 - Implements.....	117
Figure 9:27 - Capability	118
Figure 9:28 - CapabilityGeneralization	118
Figure 9:29 - ActualEnduringTask	119
Figure 9:30 - ActualEnterprisePhase	119
Figure 9:31 - CapabilityRole	120
Figure 9:32 - EnduringTask	120
Figure 9:33 - EnterpriseGoal	120
Figure 9:34 - EnterprisePhase.....	121
Figure 9:35 - EnterpriseVision	121
Figure 9:36 - StructuralPart	122
Figure 9:37 - TemporalPart	122
Figure 9:38 - VisionStatement.....	123
Figure 9:39 - WholeLifeEnterprise.....	123
Figure 9:40 - CapabilityDependency	123
Figure 9:41 - CapabilityRoleDependency	124
Figure 9:42 - AchievedEffect	124
Figure 9:43 - Achiever.....	125
Figure 9:44 - DesiredEffect	125
Figure 9:45 - Desirer.....	126
Figure 9:46 - CapabilityForTask	126
Figure 9:47 - CapableElement	127
Figure 9:48 - Exhibits	127
Figure 9:49 - MapsToCapability	128
Figure 9:50 - OrganizationInEnterprise.....	128
Figure 9:51 - ArbitraryConnector.....	129
Figure 9:52 - ConceptItem.....	129
Figure 9:53 - HighLevelOperationalConcept	130
Figure 9:54 - KnownResource.....	130
Figure 9:55 - OperationalAgent.....	131
Figure 9:56 - OperationalArchitecture.....	131
Figure 9:57 - OperationalMethod	132
Figure 9:58 - OperationalParameter	132
Figure 9:59 - OperationalPerformer	133
Figure 9:60 - OperationalRole	133
Figure 9:61 - ProblemDomain	134
Figure 9:62 - OperationalConnector	134
Figure 9:63 - OperationalExchange.....	135
Figure 9:64 - OperationalExchangeItem.....	135
Figure 9:65 - OperationalInterface	136
Figure 9:66 - OperationalPort.....	136
Figure 9:67 - OperationalSignal	137
Figure 9:68 - OperationalActivity	137
Figure 9:69 - OperationalActivityAction.....	138
Figure 9:70 - OperationalActivityEdge	138
Figure 9:71 - StandardOperationalActivity	139
Figure 9:72 - OperationalStateDescription	139
Figure 9:73 - OperationalInteractionScenario	140
Figure 9:74 - OperationalMessage.....	140
Figure 9:75 - InformationElement	141
Figure 9:76 - OperationalConstraint	141
Figure 9:77 - SubjectOfOperationalConstraint.....	141
Figure 9:78 - ServiceSpecification	142

Figure 9:79 - ServiceSpecificationGeneralization	143
Figure 9:80 - ServiceConnector	143
Figure 9:81 - ServiceMethod	144
Figure 9:82 - ServiceParameter	144
Figure 9:83 - ServiceSpecificationRole	145
Figure 9:84 - ServiceInterface	145
Figure 9:85 - ServicePort	146
Figure 9:86 - ServiceFunction	146
Figure 9:87 - ServiceFunctionAction	147
Figure 9:88 - ServiceFunctionEdge	147
Figure 9:89 - ServiceStateDescription	148
Figure 9:90 - ServiceInteractionScenario	148
Figure 9:91 - ServiceMessage	149
Figure 9:92 - ServicePolicy	149
Figure 9:93 - Consumes	150
Figure 9:94 - Organization	150
Figure 9:95 - OrganizationalResource	151
Figure 9:96 - Person	151
Figure 9:97 - Post	152
Figure 9:98 - Responsibility	152
Figure 9:99 - PostRole	153
Figure 9:100 - SubOrganization	153
Figure 9:101 - Command	154
Figure 9:102 - Control	154
Figure 9:103 - ResourceInteractionScenario	155
Figure 9:104 - Competence	155
Figure 9:105 - CompetenceForRole	156
Figure 9:106 - RequiresCompetence	156
Figure 9:107 - FillsPost	157
Figure 9:108 - CompetenceToConduct	157
Figure 9:109 - CapabilityConfiguration	158
Figure 9:110 - NaturalResource	158
Figure 9:111 - PhysicalResource	158
Figure 9:112 - ResourceArchitecture	159
Figure 9:113 - ResourceArtifact	159
Figure 9:114 - ResourcePerformer	160
Figure 9:115 - Software	160
Figure 9:116 - System	161
Figure 9:117 - ResourceMethod	161
Figure 9:118 - ResourceParameter	162
Figure 9:119 - ResourcePort	162
Figure 9:120 - ResourceRole	163
Figure 9:121 - ResourceConnector	164
Figure 9:122 - ResourceExchange	164
Figure 9:123 - ResourceExchangeItem	165
Figure 9:124 - ResourceInterface	166
Figure 9:125 - ResourceSignal	166
Figure 9:126 - Function	167
Figure 9:127 - FunctionAction	167
Figure 9:128 - FunctionEdge	168
Figure 9:129 - ResourceStateDescription	168
Figure 9:130 - ResourceMessage	169
Figure 9:131 - DataElement	169
Figure 9:132 - DataRole	170
Figure 9:133 - ResourceConstraint	170

Figure 9:134 - SubjectOfResourceConstraint	171
Figure 9:135 - Forecast	171
Figure 9:136 - SubjectOfForecast	172
Figure 9:137 - Technology	172
Figure 9:138 - VersionedElement	173
Figure 9:139 - VersionOfConfiguration	173
Figure 9:140 - VersionSuccession	174
Figure 9:141 - WholeLifeConfiguration	174
Figure 9:142 - ProtocolImplementation	175
Figure 9:143 - Asset	176
Figure 9:144 - OperationalAsset	176
Figure 9:145 - OperationalMitigation	177
Figure 9:146 - ResourceAsset	177
Figure 9:147 - ResourceMitigation	177
Figure 9:148 - SecurityEnclave	178
Figure 9:149 - AssetRole	178
Figure 9:150 - InformationRole	179
Figure 9:151 - EnhancedSecurityControl	179
Figure 9:152 - Enhances	180
Figure 9:153 - Protects	180
Figure 9:154 - ProtectsInContext	181
Figure 9:155 - SecurityProcess	181
Figure 9:156 - SecurityProcessAction	182
Figure 9:157 - ActualRisk	182
Figure 9:158 - Caveat	183
Figure 9:159 - Risk	183
Figure 9:160 - SecurityAvailability	183
Figure 9:161 - SecurityCategory	184
Figure 9:162 - SecurityClassification	184
Figure 9:163 - SecurityClassificationKind	185
Figure 9:164 - SecurityConstraint	185
Figure 9:165 - SecurityControl	186
Figure 9:166 - SecurityControlFamily	186
Figure 9:167 - SecurityIntegrity	187
Figure 9:168 - SecurityMeasurement	187
Figure 9:169 - SubjectOfSecurityConstraint	188
Figure 9:170 - Affects	188
Figure 9:171 - AffectsInContext	188
Figure 9:172 - Mitigates	189
Figure 9:173 - OwnsRisk	189
Figure 9:174 - OwnsRiskInContext	190
Figure 9:175 - Project	190
Figure 9:176 - ProjectMilestone	191
Figure 9:177 - ActualProjectMilestoneRole	191
Figure 9:178 - ProjectMilestoneRole	192
Figure 9:179 - ProjectStatus	192
Figure 9:180 - ProjectTheme	193
Figure 9:181 - StatusIndicators	193
Figure 9:182 - MilestoneDependency	194
Figure 9:183 - ProjectActivity	194
Figure 9:184 - ProjectActivityAction	194
Figure 9:185 - ProjectSequence	195
Figure 9:186 - ActualProject	195
Figure 9:187 - ActualProjectMilestone	196

ISO/IEC 19540-1: 2022

Figure 9:188 - ResponsibleFor	197
Figure 9:189 - Protocol	197
Figure 9:190 - ProtocolStack	198
Figure 9:191 - Standard	198
Figure 9:192 - ProtocolLayer	199
Figure 9:193 - ActualOrganization	199
Figure 9:194 - ActualOrganizationalResource	200
Figure 9:195 - ActualPerson	200
Figure 9:196 - ActualPost	201
Figure 9:197 - ActualResource	201
Figure 9:198 - ActualResourceRelationship	202
Figure 9:199 - ActualResponsibility	202
Figure 9:200 - ActualResponsibleResource	203
Figure 9:201 - FieldedCapability	203
Figure 9:202 - ActualService	204
Figure 9:203 - ProvidedServiceLevel	204
Figure 9:204 - ProvidesCompetence	204
Figure 9:205 - RequiredServiceLevel	205
Figure 9:206 - Alias	205
Figure 9:207 - Definition	206
Figure 9:208 - SameAs	206
Figure 9:209 - ArchitecturalDescription	207
Figure 9:210 - Architecture	208
Figure 9:211 - Concern	209
Figure 9:212 - Stakeholder	209
Figure 9:213 - UAFElement	210
Figure 9:214 - View	210
Figure 9:215 - Viewpoint	211
Figure 9:216 - DataModel	211
Figure 9:217 - ActualCondition	212
Figure 9:218 - ActualEnvironment	212
Figure 9:219 - ActualLocation	213
Figure 9:220 - ActualMeasurement	214
Figure 9:221 - ActualMeasurementSet	214
Figure 9:222 - ActualPropertySet	215
Figure 9:223 - ActualState	215
Figure 9:224 - Condition	216
Figure 9:225 - Environment	216
Figure 9:226 - GeoPoliticalExtentType	217
Figure 9:227 - ISO8601DateTime	217
Figure 9:228 - Location	218
Figure 9:229 - LocationHolder	218
Figure 9:230 - MeasurableElement	219
Figure 9:231 - Measurement	220
Figure 9:232 - MeasurementSet	220
Figure 9:233 - PropertySet	221

TABLE OF TABLES

Table 1:1 - Table of Related Documents	2
Table 5:1 - Description of acronyms used in this specification	7
Table 7:1 - Definitions for the Domains	13
Table 7:2 - Definitions of the Model Kinds	14

**Information technology – Object Management Group
Unified Architecture Framework – Part 1: Domain Metamodel (DMM)**

1 Scope

1.1 Introduction

There are four parts to this International Standard, two are normative and two informative. The normative parts are:

1. The UAF Domain Metamodel (DMM) (this document) that provides the definition of concepts, relationships and viewpoints for the framework. The UAF DMM is the basis for any implementation of UAF including non-UML/SysML implementations.
2. The UAF Profile (UAFP) (see document dtc/19-06-15) is a UML/SysML implementation of the UAF DMM

The informative parts are:

3. The UAF Traceability, Annex A (see document dtc/19-06-17), which details the mappings between the UAF and the various frameworks and languages that contribute to the UAF.
4. The UAF Example Model, Annex B (see document dtc/19-06-18), which illustrates a practical usage of UAF.

1.2 UAF Background

UAF evolved from the Unified Profile for DoDAF and MODAF (UPDM), version 2.1. UAF extends the scope of UPDM and generalizes it to make it applicable to commercial as well as military architectures. The intent of UAF is to provide a standard representation for describing enterprise architectures using a Model Based Systems Engineering (MBSE) approach.

The core concepts in the UAF are based upon the DoDAF 2.0.2 Domain Metamodel (DM2) and the MODAF ontological data exchange mechanism (MODEM), Security Views from Canada's Department of National Defense Architecture Framework (DNDAF) and the North Atlantic Treaty Organization (NATO) Architecture Framework (NAF) v 4.

UAF models describe a system¹ from a set of stakeholders' concerns such as security or information through a set of predefined viewpoints. Developed models can also reflect custom viewpoints or users can develop more formal extensions for new viewpoints.

The UAFP can be used to develop architectures compliant with:

- Department of Defense Architecture Framework (DoDAF) version 2.02
- Ministry of Defence Architecture Framework (MODAF) version 1.3
- North Atlantic Treaty Organization (NATO) Architecture Framework (NAF) version 3.1
- North Atlantic Treaty Organization (NATO) Architecture Framework (NAF) version 4

UAF v 1.1 supports the capability to:

¹ The term system is used from: "Systems and software engineering -- Architecture description," http://www.iso.org/iso/catalogue_detail.htm?csnumber=50508

- model architectures for a broad range of complex systems, which may include hardware, software, data, personnel, and facility elements,
- model consistent architectures for system-of-systems (SoS) down to lower levels of design and implementation,
- support the analysis, specification, design, and verification of complex systems; and
- improve the ability to exchange architecture information among related tools that are SysML based.

1.3 Intended Usage

The UAF enables the modeling of strategic capabilities, operational scenarios, services, resources, personnel, security, projects, standards, measures and requirements; which supports best practices through, separation of concerns and abstractions. In addition, the UAF enables the modeling of related architecture concepts such as:

- System of Systems (SoS),
- information exchanges consistent with the National Information Exchange Model (NIEM),
- DoD's doctrine, organization, training material, leadership & education, personnel, and facilities (DOTMLPF)
- UK Ministry of Defence Lines of Development (DLOD) elements,
- Human Computer Interfaces (HCI).

Further, The UAF conforms to terms defined in the ISO/IEC/IEEE 42010 standard for architecture description, where the terms: architecture, architecture description (AD), architecture framework, architecture view, architecture viewpoint, concern, environment, model kind, stakeholder [ISO/IEC/IEEE 42010:2011] form correspondence rules specified as constraints on UAF.

1.4 Related Documents

The International Standard includes a metamodel and description as separate documents. Other appendices are also provided as separate documents. The table below provides a listing of these documents:

Table 1:1 - Table of Related Documents

dtc/19-06-16	The UAF Domain MetaModel (DMM)
dtc/19-06-15	The UAF Profile (UAFP)
dtc/19-06-17	Appendix A that contains a separate traceability subsection from UAFP to each of the frameworks listed in Section 1.2 of this International Standard
dtc/19-06-18	Appendix B: An example of how the language can be used to represent a UAFP architecture
dtc/19-06-19	UAF XMI file
dtc/19-06-20	UAF XMI Measurements library
dtc/19-05-14	Attachments

2 Conformance

UAF specifies four types of conformance.

Type 1 Conformance: - UAF View specification conformance. A tool demonstrating view specification conformance shall implement a version of all the view specifications defined in the UAF Grid, with the exception of the view specifications in the Metadata Domain. Optionally the tool vendor can implement other donor framework viewpoints, for instance DoDAF, MODAF or NAF based upon the mapping between them and UAF provided in Appendix A (dte/19-06-17)

Type 2 Conformance: - UAF Conceptual Syntax Conformance. A tool demonstrating conceptual syntax conformance is consistent with the concepts, relationships and constraints defined in the UAF DMM (this document). UAF Conceptual Syntax Conformance implies Type 1 Conformance.

Type 3 Conformance: - UAF Formal Syntax Conformance. A tool demonstrating formal syntax conformance:

- enables instances of concrete UAFP stereotypes defined in the UAFP (dte/19-06-15)
- complies with the constraints defined in the UAFP (dte/19-06-15)
- complies with the SysML version 1.5 Concrete Syntax Conformance (formal/17-05-01)

UAF Formal Syntax Conformance implies Type 2 Conformance.

Type 4 Conformance: - UAF Model interchange conformance. A tool demonstrating model interchange conformance can import and export conformant XMI for all valid UAFP models. Model interchange conformance implies Type 3 Conformance.

3 References

3.1 Normative References

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply.

3.2 OMG Documents (Normative References)

- Unified Modeling Language (UML), 2.5.1, December 2017, <https://www.omg.org/spec/UML>
- Object Constraint Language (OCL), 2.4, February 2014, <https://www.omg.org/spec/OCL>
- System Modeling Language (SysML) ,1.5, May 2017, <https://www.omg.org/spec/SysML>
- Diagram Definition (DD), 1.1, June 2015, <https://www.omg.org/spec/DD>
- UML Profile for the National Information Exchange Model (NIEM UML), 3.0, April 2017, <https://www.omg.org/spec/NIEM-UML>
- Unified Profile for DoDAF and MODAF (UPDM), 2.1, August 2013, <https://www.omg.org/spec/UPDM>
- UML Profile for BPMN Processes, 1.0, July 2014, <https://www.omg.org/spec/BPMNProfile>
- Ontology Definition Metamodel (ODM), 1.1, September 2014, <https://www.omg.org/spec/ODM>
- Information Exchange Packaging Policy Vocabulary (IEPPV) 1.0, May 2015, <https://www.omg.org/spec/IEPPV>

3.3 Other Normative References

- Department of Defense Architecture Framework (DoDAF), Version 2.02, August 2010, <http://dodcio.defense.gov/Library/DoDArchitectureFramework.aspx>
- DM2 - DoDAF Meta-Model,
- The DM2 Conceptual Data Model, http://dodcio.defense.gov/Library/DoDArchitectureFramework/dodaf20_conceptual.aspx
- DM2 Logical Data Model, http://dodcio.defense.gov/Library/DoDArchitectureFramework/dodaf20_logical.aspx
- DM2 Formal Ontology. http://dodcio.defense.gov/Library/DoDArchitectureFramework/dodaf20_ontology1.aspx
- Department National Defence and Canadian Forces (DND/ CF) Architecture Framework (DNDAF), Version 1.8.1, 25 January 2013
- International Defence Enterprise Architecture Specification for Exchange (IDEAS) Group, <http://www.ideasgroup.org/>
- IDEAS Foundation, <http://www.ideasgroup.org/foundation/>
- IDEAS Foundation v1.0 as XMI File (zipped), <http://www.ideasgroup.org/7Documents/>
- ISO/IEC/IEEE 42010:2011, Systems and software engineering – Architecture Description, http://www.iso.org/iso/catalogue_detail.htm?csnumber=50508
- Ministry of Defence Architecture Framework (MODAF), <https://www.gov.uk/mod-architecture-framework>
- MODAF Ontological Data Exchange Mechanism (MODEM)
- https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/63980/20130117_MODAF_MO_DEM.pdf
- NATO Architecture Framework (NAF),

ISO/IEC 19540-1: 2022

- Version 3, NATO C3 BOARD (AC/322-D(2007)0048), <http://www.nhq3s.nato.int/HomePage.asp> (no longer publicly available online as of 3 November 2015)
- NATO Architecture Framework v4.0 Documentation.

3.4 Informative References

- Business Process Model & Notation (BPMN), Version 2.0.2, January 2014 <https://www.omg.org/spec/BPMN>
- ISO 15704:2000, Industrial Automation Systems – “Requirements for Enterprise-Reference Architectures and Methodologies,” http://www.iso.org/iso/home/store/catalogue_tc/catalogue_detail.htm?csnumber=28777
- ISO 8601:2004 Data elements and interchange formats – Information interchange – Representation of dates and times,
http://www.iso.org/iso/home/store/catalogue_ics/catalogue_detail_ics.htm?ics1=01&ics2=140&ics3=30&csnumber=40874
- ISO/IEC 15288:2015, "Systems Engineering - Systems Life Cycle Processes,"
http://www.iso.org/iso/home/store/catalogue_tc/catalogue_detail.htm?csnumber=63711
- Object Management Group (OMG), Metamodel Extension Facility, Initial submission, ad/12-02-01,
<https://www.omg.org/cgi-bin/doc?ad/12-02-01> (Requires OMG Member Access)
- OASIS SOA-RAF, Reference Architecture Foundation for Service Oriented Architecture Version 1.0, OASIS SOA Reference Model TC, 04 December 2012. <http://docs.oasis-open.org/soa-rm/soa-ra/v1.0/cs01/soa-ra-v1.0-cs01.pdf> (Authoritative)
- Object Management Group (OMG), Semantics of Business Vocabulary and Business Rules (SBVR), Version 1.3, May 2015, <https://www.omg.org/spec/SBVR>
- Business Motivation Model (BMM), Version 1.3, <http://www.omg.org/spec/BMM/1.3/>
- International Council On Systems Engineering (INCOSE), Systems Engineering Handbook V4, 2015,
<http://www.incose.org/ProductsPublications/sehandbook>

4 Terms and Definitions

No new terms and definitions have been required to create this International Standard. All terms are available in the normative references or bibliographic citations for detailed explanation.

5 Symbols

For the purposes of this International Standard, the following List of symbols/abbreviations apply.

Table 5:1 - Description of acronyms used in this International Standard

AcV-* ²	Acquisition View
AD	Architecture Description
AV-*	All View
BMM	Business Motivation Model
BPMN	Business Process Modeling Notation
C4ISR	Command, Control, Communications, Computers, Intelligence, Surveillance, and Reconnaissance
CaT	Capability Team
COI	Communities of Interest
CV-*	Capability View
DIV-*	Data and Information Views
DLOD	Defence Lines of Development
DM2	DoDAF Meta Model
DMM	Domain Meta Model
DNDAF	Department National Defence and Canadian Forces (DND/ CF) Architecture Framework
DoD	United States Department of Defense
DoDAF	Department of Defense Architecture Framework
DOTMLP	Doctrine, Organization, Training, Material, Leadership, Personnel, Facilities
EIE	Enterprise Information Environment
IDEAS	International Defense Enterprise Architecture Specification for Exchange
IDEF	Integrated DEFinition Methods
INCOSE	International Council Of Systems Engineering
JCIDS	Joint Capabilities Integration and Development System
MISIG	Model Interchange Special Interest Group
MOD	United Kingdom Ministry of Defence
MODAF	Ministry of Defence Architecture Framework
MODEM	MODAF Ontological Data Exchange Mechanism
NAF	NATO Architecture Framework
OASIS	Organization for the Advancement of Structured Information Standards
OSLC	Open Services for Lifecycle Collaboration
OV-*	Operational View
PES	DoDAF Physical Exchange Specification
POC	Proof of Concept
PV-*	Project View
RDF	Resource Description Framework
SoaML	Service orientated architecture Modeling Language
SoS	System of Systems

² * denotes a wildcard

SOV-*	Service Oriented View
StdV-*	Standards View in DoDAF 2.02 compare TV-* in UAF
STV-*	Strategic View
SV-*	System View
SvcV-*	Service View
TEPID OIL	Training, Equipment, Personnel, Information, Concepts and Doctrine, Organisation, Infrastructure, Logistics
TOGAF	The Open Group Architectural Framework©
TPPU	Task, Post, Process, and Use
TV-*	Technical View
UAF	Unified Architecture Framework
UAFP	Unified Architecture Framework Profile
UPDM	Unified Profile for DoDAF/MODAF

6 Additional Information

6.1 Changes to Adopted OMG Specifications

This specification completely replaces Unified Architecture Framework (UAF), version 1.0
<https://www.omg.org/spec/UAF/About-UAF/>

6.2 Language Architecture

The UAF specification reuses a subset of UML 2.5.1 and SysML 1.5 and provides additional extensions needed to address requirements in the UPDM 3.0 RFP Mandatory Requirements. Those requirements form the basis for this specification. This specification documents the language architecture in terms of UML 2.5.1 and SysML 1.5 and specifies how to implement UAF. This clause explains design principles and how they are applied to define the UAF language architecture.

6.3 Philosophy

The UAF development uses a model-driven approach. A simple description of the work process is:

- A Domain Metamodel (DMM) uses UML Class models to represent individuals, types and tuples that aggregate the concepts defined in DoDAF, MODEM, NAF, DNDAF and other frameworks.
- The aligned and renamed viewpoints from the various frameworks provide a common generic name for each viewpoint. It should be noted that the term viewpoint is in the context of ISO 42010 where a viewpoint is the specification of a view. The UAF viewpoints are mapped to the corresponding viewpoint in the relevant contributing framework. It is the viewpoints described in the DMM that provides the basis for the Unified Architecture Framework (UAF).
- The UAF provides an abstraction layer that separates the underlying UAF metamodel from the presentation layer. The results of this mapping are given in Appendix A (see document dtc/19-06-17 and an overview of the viewpoints in a grid format are given in this docume.
- The intent of the UAF is to provide a Domain MetaModel usable by non-UML/SysML tool vendors who may wish to implement the UAF within their own tool and metalanguage.
- The Unified Architecture Framework Profile (UAFP) is the standard implementation of the UAF DMM. It was created by mapping the UAF concepts and relationships to corresponding stereotypes in the UAFP.
- The UAFP analysis and refactoring reflects language architecture, tool implementation, and reuse considerations.
- The specification is generated from the UML model used to describe the UAF DMM and UAFP. This approach allows the team to concentrate on architecture issues rather than documentation production. The UML tool automatically maintains consistency. The UML tool improves maintenance and enables traceability between the UAF and the UAFP where every stereotype is linkable to the UAF element using UML Abstraction relationship.

6.4 Core Principles

The fundamental design principles for UAF DMM are:

- **Requirements-driven:** UAF is intended to satisfy the requirements of the UPDM 3.0 RFP Mandatory Requirements.
- **Influence from donor Frameworks:** The DMM was based upon an aggregation of concepts and relationships from the donor frameworks.
- **IDEAS Ontology driven:** The DMM was based upon a simplified version of the IDEAS ontology, see chapter 8.

- **DMM Notation:** The DMM was expressed using UML class diagram notation.
- **Reusability of UML Metamodel concepts:** The UAF DMM reuses a number of concepts from the UML Metamodel, such as Statemachines, Activities and Interactions. The explicit relationship to these concepts enables the UAF DMM to reuse UML semantics instead of reinventing its own semantics.
- **Reusability of BPMN concepts:** The UAF DMM reuses a number of concepts from BPMN, such as processes. The explicit relationship to these concepts enables the UAF DMM to reuse BPMN semantics instead of reinventing its own semantics.

7 UAF Grid

Due to the complexity of managing the multiple viewpoints with overlapping concerns and metamodels, the standard viewpoints are refactored as described in the donor frameworks into a more manageable format. This decision led to the development of the UAF grid which is described below.

The grid is a way of showing how the various viewpoints (known as *view specifications* in the rest of document) correspond to *domains* (horizontal rows) and the *model kinds* (the columns) that describe the view specification. The intent of the grid is not to be complete, but to capture the information that is present in the frameworks that contributes to the UAF, consequently, some gaps are evident.

	Taxonomy Tx	Structure Sr	Connectivity Cn	Processes Pr	States St	Interaction Scenarios Is	Information ^c If	Parameters ^d Pm	Constraints Ct	Roadmap Rm	Traceability Tr
Metadata^a Md	Metadata Taxonomy Md-Tx ^f	Metadata Structure Md-Sr	Metadata Connectivity Md-Cn	Metadata Processes Md-Pr	Metadata States Md-St	-	Conceptual Data Model,	Environment Pm-En	Metadata Constraints Md-Ct	Metadata Roadmap Md-Rm	Metadata Traceability Md-Tr
Strategic St	Strategic Taxonomy St-Tx	Strategic Structure St-Sr	Strategic Connectivity St-Cn	-	Strategic States St-St	-			Strategic Constraints St-Ct	Strategic Deployment, St-Rm, Strategic Phasing St-Rm	Strategic Traceability St-Tr
Operational Op	Operational Taxonomy Op-Tx	Operational Structure Op-Sr	Operational Connectivity Op-Cn	Operational Processes Op-Pr	Operational States Op-St	Operational Interaction Scenarios Op-Is			Operational Constraints Op-Ct	-	Operational Traceability Op-Tr
Services Sv	Service Taxonomy Sv-Tx	Service Structure Sv-Sr	Service Connectivity Sv-Cn	Service Processes Sv-Pr	Service States Sv-St	Service Interaction Scenarios Sv-Is			Service Constraints Sv-Ct	Service Roadmap Sv-Rm	Service Traceability Sv-Tr
Personnel Pr	Personnel Taxonomy Pr-Tx	Personnel Structure Pr-Sr	Personnel Connectivity Pr-Cn	Personnel Processes Pr-Pr	Personnel States Pr-St	Personnel Interaction Scenarios Pr-Is	Logical Data Model,	Measurements Pm-Me	Competence, Drivers, Performance Pr-Ct	Personnel Availability, Personnel Evolution, Personnel Forecast Pr-Rm	Personnel Traceability Pr-Tr
Resources Rs	Resource Taxonomy Rs-Tx	Resource Structure Rs-Sr	Resource Connectivity Rs-Cn	Resource Processes Rs-Pr	Resource States Rs-St	Resource Interaction Scenarios Rs-Is	Physical schema ^e , real world results		Resource Constraints Rs-Ct	Resource evolution, Resource forecast Rs-Rm	Resource Traceability Rs-Tr
Security Sc	Security Taxonomy Sc-Tx	Security Structure Sc-Sr	Security Connectivity Sc-Cn	Security Processes Sc-Pr	-	-	Security Constraints Sc-Ct		-	Security Traceability Sc-Tr	
Projects Pj	Project Taxonomy Pj-Tx	Project Structure Pj-Sr	Project Connectivity Pj-Cn	Project Processes Pj-Pr	-	-	-		Project Roadmap Pj-Rm	Project Traceability Pj-Tr	
Standards Sd	Standard Taxonomy Sd-Tx	Standards Structure Sd-Sr	-	-	-	-	-	-	Standards Roadmap Sd-Rm	Standards Traceability Sd-Tr	
Actual Resources Ar	-	Actual Resources Structure Ar-Sr	Actual Resources Connectivity Ar-Cn	Simulation ^b			-	Parametric Execution/ ^b Evaluation	-	-	
Dictionary Dc											
Summary & Overview Sm-Ov											
Requirements Req											

Figure 7:7-1- UAF Grid

Notes related to suffixes in the grid:

- The view specifications in the Metadata Domain are not modeled as part of the UAF but are architectural artifacts that contribute to the success in defining and developing an architecture.
- To be able to evaluate architecture behavior and constraints (i.e., non-functional requirements) it is necessary to define actual instances of the architectural elements. The expectation is that tool vendors intending to implement the UAF have capabilities native to their tools to enable behavioral simulation and the evaluation of measures and constraints through parametric diagrams or a proprietary equivalent.
- The information model is a column across the domains and can be defined in any of its forms, i.e., Conceptual, Logical or Physical. The expectation is that most developers of the information model will use the Conceptual or Logical forms of the data model when using an abstract modeling tool.

- d. The parameters column captures the measures and environments across the architecture in all the different domains.
- e. The expectation is that the physical schema model would not be defined in the UAF. Any tool implementing the framework provides a means to import or link-to representations of the physical model.
- f. The Metadata Taxonomy view specification provides a means to extend the framework to other domains.

The detailed mapping between the view specifications of the UAF shown in the grid and the viewpoints from the donor frameworks is described in [dte\2019-06-17](#). A definition for each view specification in the grid is described in the following chapters.

7.1 Descriptions of Domains and Model Kinds

Table 7:1 - Definitions for the Domains

Domain	Acronym	Description
Metadata	Md	Identifies the metadata required to develop a suitable architecture that is fit for its purpose.
Strategic	St	Capability management process. Describes the capability taxonomy, composition, dependencies and evolution.
Operational	Op	Illustrates the Logical Architecture of the enterprise. Describes the requirements, operational behavior, structure, and exchanges required to support (exhibit) capabilities. Defines all operational elements in an implementation/solution independent manner.
Services	Sv	The Service-Orientated View (SOV) is a description of services needed to directly support the operational domain as described in the Operational View. A service within MODAF is understood in its broadest sense, as a unit of work through which a provider provides a useful result to a consumer. DoDAF: The Service Views within the Services Viewpoint describe the design for service-based solutions to support operational development processes (JCIDS) and Defense Acquisition System or capability development within the Joint Capability Areas.
Personnel	Pr	Defines and explores organizational resource types. Shows the taxonomy of types of organizational resources as well as connections, interaction and growth over time.
Resources	Rs	Captures a solution architecture consisting of resources, e.g., organizational, software, artifacts, capability configurations, and natural resources that implement the operational requirements. Further design of a resource is typically detailed in SysML or UML.
Security	Sc	Security assets and security enclaves. Defines the hierarchy of security assets and asset owners, security constraints (policy, laws, and guidance) and details where they are located (security enclaves).
Projects	Pj	Describes projects and project milestones, how those projects deliver capabilities, the organizations contributing to the projects and dependencies between projects.
Standards	Sd	MODAF: Technical Standards Views are extended from the core DoDAF views to include non-technical standards such as operational doctrine, industry process standards, etc. DoDAF: The Standards Views within the Standards Viewpoint are the set of rules governing the arrangement, interaction, and interdependence of solution parts or elements.
Actual Resources	Ar	The analysis, e.g., evaluation of different alternatives, what-if, trade-offs, V&V on the actual resource configurations. Illustrates the expected or achieved actual resource configurations.

Table 7:2 - Definitions of the Model Kinds

Model Kind	Acronym	Description
Taxonomy	Tx	Presents all the elements as a standalone structure. Presents all the elements as a specialization hierarchy, provides a text definition for each one and references the source of the element
Structure	Sr	Describes the definitions of the dependencies, connections, and relationships between the different elements.
Connectivity	Cn	Describes the connections, relationships, and interactions between the different elements.
Processes	Pr	Captures activity based behavior and flows. It describes activities, their Inputs/Outputs, activity actions and flows between them.
States	St	Captures state-based behavior of an element. It is a graphical representation of states of a structural element and how it responds to various events and actions.
Interaction Scenarios	Is	Expresses a time ordered examination of the exchanges as a result of a particular scenario. Provides a time-ordered examination of the exchanges between participating elements as a result of a particular scenario.
Information	If	Address the information perspective on operational, service, and resource architectures. Allows analysis of an architecture's information and data definition aspect, without consideration of implementation specific issues.
Constraints	Ct	Details the measurements that set performance requirements constraining capabilities. Also defines the rules governing behavior and structure.
Roadmap	Rm	Addresses how elements in the architecture change over time. Also, how at different points in time or different periods of time.
Traceability	Tr	Describes the mapping between elements in the architecture. This can be between different viewpoints within domains as well as between domains. It can also be between structure and behaviors.

7.2 Domain Interrelationships

Although the grid is the primary means of expressing the relationship between the Domains, Model Kinds and View Specifications, because of its two-dimensional nature it is not adequate to explain the abstract interrelationships that exist between the domains. The following diagram is an indication of how the domains are interrelated.




Figure 7:7-2 - Domain Interrelationships

Where a Domain is shown vertically the intent is to show that the Domain is a cross cutting concern that goes across the levels of abstraction in the architecture.

Where a Domain is shown horizontally the intent is to show that the Domain exists in a layer of abstraction between the Domains above and below it and there is an interrelationship with the Domains either side of it.

7.3 Domain Metamodel Diagram Legend

This Annex comprises of various diagrams that document the Domain Metamodel (DMM) that document the MoDAF 1.5 and MoDAF 1.2 integrated model. This model was used as a basis for creating the UPDM profile.

Note that the diagrams rely on color to aid the reader in understanding the model. Please refer to the legend below to understand the diagrams.

The following is the legend of element colors used in the DMM and what they denote.




Figure 7:7-3 - Legend of color codes for element types defined in UAF

The meaning of the element types in the UAF are based upon concepts put forth in the International Defence Enterprise Architecture Specification (IDEAS).

- An Individual denotes a single instance of an element.
- A Type denotes a set of Individuals.
- A Tuple denotes a relationship that exists between elements.
- An Abstract denotes that the element has no direct use but is a means of construction.
- An Enumeration is a complete, ordered listing of all the items in a collection.
- An External Type is an element that exists outside of the core DMM but is referenceable by elements in the DMM.

8 Domain Metamodel Diagrams

Note that the diagrams rely on color to aid the reader in understanding the model. Please refer to the legend in the various diagrams to understand the specific definitions.

8.1 View Specifications

This section documents each of the view specifications of UAF.

8.1.1 View Specifications::Metadata

Stakeholders: Enterprise Architects, Technical Managers.

Concerns: architecture development process, architecture traceability, metamodel and its extensions, architecture versioning.

Definition: Identifies the metadata required to develop a suitable architecture that is fit for its purpose.

View Specifications::Metadata::Taxonomy

Stakeholders: Enterprise Architects, Technical Managers.

Concerns: metamodel and its extensions.

Definition: captures user defined metamodel extensions

Recommended Implementation: UML Profile Diagram, SysML Block Definition Diagram

View Specifications::Metadata::Structure

Stakeholders: Enterprise Architects, Technical Managers.

Concerns: domains, model kinds, and view specifications that are used to describe the architecture.

Definition: (i) lists predefined and custom domains, model kinds, and view specifications (ii) and identify the key stakeholders and their concerns.

Recommended Implementation: SysML Block Definition Diagram, SysML Package Diagram.

View Specifications::Metadata::Connectivity

Stakeholders: Enterprise Architects, people who want to understand relationships to related architectural descriptions, Technical Managers.

Concerns: high-level dependencies between architectural descriptions.

Definition: depicts and analyzes all relevant dependencies between architectural descriptions, e.g., reference architectures, as-is to to-be architectures.

Recommended Implementation: SysML Block Definition Diagram, SysML Package Diagram, matrix format.

View Specifications::Metadata::Processes

Stakeholders: Enterprise Architects, people who want to understand the architecture development process, Technical Managers.

Concerns: methodology used.

Definition: methodology used in developing the architecture.

Recommended Implementation: SysML Activity Diagram, text.

View Specifications::Metadata::States

Stakeholders: Enterprise Architects, people who want to understand the architecture governance, Technical Managers.

Concerns: architecture status.

Definition: captures version number and approval workflow of the architecture.

Recommended Implementation: SysML State Machine Diagram, state table, text.

View Specifications::Metadata::Constraints

Stakeholders: Enterprise Architects, people who want to understand constraints for the architecture, Technical Managers.

Concerns: architectural constraints.

Definition: captures assumptions and constraints on the architecture.

Recommended Implementation: tabular format, text.

View Specifications::Metadata::Roadmap

Stakeholders: Enterprise Architects, people who want to understand the architecture development plan, Technical Managers.

Concerns: architecture release schedule.

Definition: captures project timeline for the architecture.

Recommended Implementation: timeline, text.

View Specifications::Metadata::Traceability

Stakeholders: Enterprise Architects, people who want to understand impact of change across the architecture supporting assets, Technical Managers.

Concerns: reuse of architectures.

Definition: shows references to asset libraries, legacy architectures, and external sources, e.g., documents.

Recommended Implementation: SysML Block Definition Diagram, SysML Package Diagram, tabular format.

8.1.2 View Specifications::Strategic

Stakeholders: Capability Portfolio Managers.

Concerns: capability management process.

Definition: describe capability taxonomy, composition, dependencies and evolution.

View Specifications::Strategic::Taxonomy

Contains the diagrams that document the Strategic Taxonomy Viewpoint.

View Specifications::Strategic::Taxonomy::Strategic Taxonomy

Stakeholders: PMs, Enterprise Architects, Executives.

Concerns: capability needs.

Definition: shows the taxonomy of capabilities.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8-1 Strategic Taxonomy

Elements

- [Capability](#)
- [CapabilityGeneralization](#)
- [CapabilityRole](#)

View Specifications::Strategic::Structure

Contains the diagrams that document the Strategic Structure Viewpoint.

View Specifications::Strategic::Structure::Strategic Structure

Stakeholders: PMs, Enterprise Architects, Executives.

Concerns: capability needs.

Definition: shows the relationship between EnterprisePhases and the Capabilities that are intended to be developed during the enterprise phases, and the organizations involved in the enterprise.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:2 - Strategic Structure

Elements

- [ActualEnduringTask](#)
- [ActualEnterprisePhase](#)
- [ActualOrganization](#)
- [ActualResponsibleResource](#)
- [Capability](#)
- [CapableElement](#)
- [EnduringTask](#)
- [Enterprise](#)
- [EnterprisePhase](#)
- [EnterpriseVision](#)
- [Exhibits](#)
- [OperationalArchitecture](#)
- [OrganizationInEnterprise](#)
- [ResourceArchitecture](#)
- [StructuralPart](#)
- [TemporalPart](#)
- [WholeLifeEnterprise](#)

View Specifications::Strategic::Connectivity

Contains the diagrams that document the Strategic Connectivity Viewpoint.

View Specifications::Strategic::Connectivity::Strategic Connectivity

Stakeholders: PMs, Executives, Enterprise Architects.

Concerns: capability dependencies.

Definition: describes the dependencies between planned capabilities.

Recommended Implementation: SysML Block Definition Diagram. SysML Internal Block Diagram.




Figure 8:3 - Strategic Connectivity

Elements

- [Capability](#)
- [CapabilityDependency](#)
- [CapabilityRole](#)
- [CapabilityRoleDependency](#)

View Specifications::Strategic::States

Contains the diagrams that document the Strategic States Viewpoint.

View Specifications::Strategic::States::Strategic States

Stakeholders: PMs, Enterprise Architects.

Concerns: effects that the implementation(s) of capabilities are expected to deliver.

Definition: captures the relationships between capability(ies) and desired effect(s) that implementation(s) of capability(ies) should achieve.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:4 - Strategic States

Elements

- [AchievedEffect](#)
- [Achiever](#)
- [ActualOrganization](#)
- [ActualOrganizationalResource](#)
- [ActualPerson](#)
- [ActualPost](#)
- [ActualResource](#)
- [ActualResponsibleResource](#)
- [ActualState](#)
- [Capability](#)
- [CapabilityConfiguration](#)
- [DesiredEffect](#)
- [Desirer](#)
- [FieldedCapability](#)
- [NaturalResource](#)
- [OperationalAgent](#)
- [OperationalPerformer](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [ResourceArchitecture](#)

- [ResourceArtifact](#)
- [ResourceMitigation](#)
- [ResourcePerformer](#)
- [Software](#)
- [Technology](#)

View Specifications::Strategic::Constraints

Contains the diagrams that document the Strategic Constraints Viewpoint.

View Specifications::Strategic::Constraints::Strategic Constraints

Stakeholders: PMs, Enterprise Architects.

Concerns: capability constraints.

Definition: details the measurements that set performance requirements constraining capabilities.

Recommended Implementation: tabular format, SysML Block Definition Diagram.




Figure 8:5 - Strategic Constraints

Elements

- [Capability](#)
- [Measurement](#)
- [PropertySet](#)

View Specifications::Strategic::Roadmap

Contains the diagrams that document the Strategic Roadmap Viewpoint.

View Specifications::Strategic::Roadmap::Deployment

View Specifications::Strategic::Roadmap::Deployment::Strategic Roadmap: Deployment

Stakeholders: PMs, Executives, Enterprise Architects.

Concerns: capability deployment to organizations over time.

Definition: addresses the deployment of capability(ies) to actual organizations over time.

Recommended Implementation: timeline, tabular format, SysML Block Definition Diagram.




Figure 8:6 - Strategic Roadmap: Deployment

Elements

- [ActualEnterprisePhase](#)
- [ActualOrganization](#)
- [ActualPerson](#)
- [ActualPost](#)
- [ActualProject](#)
- [ActualProjectMilestone](#)
- [ActualResource](#)
- [ActualResponsibleResource](#)
- [Capability](#)
- [CapabilityConfiguration](#)
- [CapableElement](#)
- [EnterprisePhase](#)
- [Exhibits](#)
- [ResourceArchitecture](#)
- [ResourcePerformer](#)
- [ResponsibleFor](#)
- [VersionedElement](#)

View Specifications::Strategic::Roadmap::Phasing

View Specifications::Strategic::Roadmap::Phasing::Strategic Roadmap: Phasing

Stakeholders: PMs, Executives, Enterprise Architects.

Concerns: capability(ies) achievement over time.

Definition: the planned achievement of capability(ies) at different points in time or during specific periods of time.

Recommended Implementation: timeline, tabular format, SysML Block Definition Diagram.




Figure 8:7 - Strategic Roadmap: Phasing

Elements

- [ActualProject](#)
- [ActualProjectMilestone](#)
- [ActualResource](#)
- [Capability](#)
- [CapabilityConfiguration](#)
- [CapableElement](#)
- [Exhibits](#)
- [FieldedCapability](#)
- [Project](#)
- [ResourceArchitect](#)
- [ResourcePerformer](#)
- [VersionedElement](#)

View Specifications::Strategic::Traceability

Contains the diagrams that document the Strategic Traceability Viewpoint.

View Specifications::Strategic::Traceability::Strategic Traceability

Stakeholders: PMs, Enterprise Architects, Business Architects.

Concerns: traceability between capabilities and operational activities.

Definition: describes the mapping between the capabilities required by an Enterprise and the supporting operational activities.

Recommended Implementation: matrix format, SysML Block Definition Diagram.




Figure 8:8 - Strategic Traceability

Elements

- [ActualEnduringTask](#)
- [Capability](#)
- [CapabilityForTask](#)
- [Function](#)
- [Implements](#)
- [MapsToCapability](#)
- [OperationalActivity](#)
- [Process](#)
- [StandardOperationalActivity](#)

8.1.3 View Specifications::Operational

Stakeholders: Business Architects, Executives.

Concerns: illustrate the Logical Architecture of the enterprise.

Definition: describe the requirements, operational behavior, structure, and exchanges required to support (exhibit) capabilities. Defines all operational elements in an implementation/solution independent manner.

View Specifications::Operational::Taxonomy

Contains the diagrams that document the Operational Taxonomy Viewpoint.

View Specifications::Operational::Taxonomy::Operational Taxonomy

Stakeholders: Business Architects, Systems Engineers, Enterprise Architects, Owners responsible for Operational Agents.

Concerns: OperationalAgent types.

Definition: shows the taxonomy of types of OperationalAgents.

Recommended Implementation: SysML Block Definition Diagram, SysML Internal Block Diagram.




Figure 8:9 - Operational Taxonomy

Elements

- [ArbitraryConnector](#)
- [Asset](#)
- [CapabilityConfiguration](#)
- [ConceptItem](#)
- [HighLevelOperationalConcept](#)
- [Location](#)
- [NaturalResource](#)
- [OperationalAgent](#)
- [OperationalAsset](#)
- [OperationalPerformer](#)
- [Organization](#)
- [OrganizationalResource](#)
- [PhysicalResource](#)
- [Post](#)
- [ResourceArchitecture](#)
- [ResourceArtifact](#)
- [ResourceAsset](#)
- [ResourcePerformer](#)
- [Software](#)

View Specifications::Operational::Structure

Contains the diagrams that document the Operational Structure Viewpoint.

View Specifications::Operational::Structure::Operational Structure

Stakeholders: Business Architects, Systems Engineers, Enterprise Architects, Owners responsible for Operational Agents.

Concerns: identifies the operational exchange requirements between nodes.

View Specifications::Operational::Connectivity::Operational Connectivity

Stakeholders: Systems Engineers, Architects, Solution Providers.

Concerns: capture the interfaces between OperationalPerformers.

Definition: summarizes logical exchanges between OperationalPerformers of information, systems, personnel, energy etc. and the logical activities that produce and consume them. Measurements can optionally be included.

Recommended Implementation: SysML Internal Block Diagram, tabular format.




Figure 8:11 - Operational Connectivity

Elements

- [CapabilityConfiguration](#)
- [Exchange](#)
- [GeoPoliticalExtentType](#)
- [InformationElement](#)
- [IsCapableToPerform](#)
- [MeasurableElement](#)
- [MeasurementSet](#)
- [NaturalResource](#)
- [OperationalActivity](#)
- [OperationalActivityAction](#)
- [OperationalActivityEdge](#)
- [OperationalAgent](#)
- [OperationalConnector](#)
- [OperationalExchange](#)
- [OperationalExchangeItem](#)
- [OperationalInterface](#)
- [OperationalPerformer](#)
- [OperationalPort](#)

- [OperationalRole](#)
- [OperationalSignal](#)
- [OrganizationalResource](#)
- [PhysicalResource](#)
- [ResourceArchitecture](#)
- [ResourceArtifact](#)
- [ResourcePerformer](#)

View Specifications::Operational::Processes

Contains the diagrams that document the Operational Processes Viewpoint.

View Specifications::Operational::Processes::Operational Processes

Stakeholders: Business Architect, Systems Engineers, Enterprise Architects

Concerns: captures activity based behavior and flows.

Definition: describes the activities that are normally conducted in the course of achieving business goals that support a capability. It describes operational activities, their Inputs/Outputs, operational activity actions and flows between them.
 Recommended Implementation: SysML Activity Diagram, SysML Block Definition Diagram.




Figure 8:12 - Operational Processes

Elements

- [ActivityPerformableUnderCondition](#)
- [ActualCondition](#)
- [ActualMeasurementSet](#)
- [ActualService](#)
- [IsCapableToPerform](#)
- [MeasurableElement](#)
- [OperationalActivity](#)
- [OperationalActivityAction](#)
- [OperationalActivityEdge](#)
- [OperationalAgent](#)
- [OperationalExchange](#)
- [OperationalExchangeItem](#)
- [OperationalMethod](#)
- [OperationalParameter](#)
- [OperationalPerformer](#)
- [OperationalRole](#)
- [PerformsInContext](#)
- [Process](#)
- [ProcessEdge](#)
- [ProcessOperation](#)
- [ProcessParameter](#)
- [ProcessUsage](#)
- [RequiredServiceLevel](#)
- [ServiceSpecification](#)
- [StandardOperationalActivity](#)
- UML2.5Metamodel::Activity
- UML2.5Metamodel::ActivityEdge
- UML2.5Metamodel::CallBehaviorAction
- UML2.5Metamodel::Operation
- UML2.5Metamodel::Parameter

View Specifications::Operational::Processes::Operational Processes BPMN Semantics

Stakeholders: Business Architect, Enterprise Architects.

Concerns: captures activity based behavior and flows using BPMN notation.

Definition: describes the BPMN processes that are normally conducted in the course of achieving business goals that support a capability. It describes operational activities, their Inputs/Outputs, operational activity actions and flows between them using BPMN notation.

Recommended Implementation: BPMN Process Diagram.




Figure 8:13 - Operational Processes BPMN Semantics

Elements

- [ActivityPerformableUnderCondition](#)
- [ActualCondition](#)
- [ActualEnduringTask](#)
- [ActualMeasurementSet](#)
- [ActualService](#)
- [AssetRole](#)
- BPMN2Metamodel::BPMNMessage
- BPMN2Metamodel::CallActivity
- BPMN2Metamodel::MessageFlow
- BPMN2Metamodel::Process
- BPMN2Metamodel::ResourceRole
- BPMN2Metamodel::SequenceFlow
- [EnduringTask](#)
- [Exchange](#)
- [ExchangeItem](#)
- [Implements](#)
- [IsCapableToPerform](#)
- [MeasurableElement](#)
- [OperationalActivity](#)
- [OperationalActivityAction](#)
- [OperationalActivityEdge](#)

- [OperationalAgent](#)
- [OperationalExchange](#)
- [OperationalExchangeItem](#)
- [OperationalMethod](#)
- [OperationalParameter](#)
- [OperationalPerformer](#)
- [OperationalRole](#)
- [PerformsInContext](#)
- [Process](#)
- [ProcessEdge](#)
- [ProcessUsage](#)
- [RequiredServiceLevel](#)
- [ServiceSpecification](#)
- [StandardOperationalActivity](#)

View Specifications::Operational::States

Contains the diagrams that document the Operational States Viewpoint.

View Specifications::Operational::States::Operational States

Stakeholders: Systems Engineers, Software Engineers.

Concerns: capture state-based behavior of an operational OperationalPerformer.

Definition: it is a graphical representation of states of an operational OperationalPerformer and how that operational OperationalPerformer responds to various events and actions.

Recommended Implementation: SysML State Machine Diagram.




Figure 8:14 - Operational States

Elements

- [OperationalAgent](#)
- [OperationalStateDescription](#)
- [StateDescription](#)
- UML2.5Metamodel::StateMachine

View Specifications::Operational::Interaction Scenarios

Contains the diagrams that document the Operational Interaction Scenarios Viewpoint.

View Specifications::Operational::Interaction Scenarios::Operational Interaction Scenarios

Stakeholders: Systems Engineers, Business Architects.

Concerns: express a time ordered examination of the operational exchanges as a result of a particular operational scenario.

Definition: provides a time-ordered examination of the operational exchanges between participating nodes (OperationalPerformer roles) as a result of a particular operational scenario.

Recommended Implementation: SysML Sequence Diagram, BPMN Collaboration Diagram.




Figure 8:15 - Operational Interaction Scenarios

Elements

- [InteractionMessage](#)
- [InteractionRole](#)
- [InteractionScenario](#)
- [OperationalActivity](#)
- [OperationalAgent](#)
- [OperationalExchange](#)
- [OperationalInteractionScenario](#)
- [OperationalMessage](#)
- [OperationalMethod](#)
- [OperationalPerformer](#)
- [OperationalRole](#)
- UML2.5Metamodel::Interaction
- UML2.5Metamodel::Lifeline
- UML2.5Metamodel::Message

View Specifications::Operational::Constraints

Contains the diagrams that document the Operational Constraints Viewpoint.

View Specifications::Operational::Constraints::Operational Constraints

Stakeholders: Systems Engineers, Architects, Program Sponsors

Concerns: define operational limitations, constraints and performance parameters for the enterprise.

Definition: specifies traditional textual operational or business rules that are constraints on the way that business is done in the enterprise. The addition of SysML parametrics provides a computational means of defining operational constraints across the enterprise or within a specific operational context.

Recommended Implementation: tabular format, SysML Block Definition Diagram, SysML Parametric Diagram.




Figure 8:16 - Operational Constraints

Elements

- [DataModel](#)
- [InformationElement](#)
- [OperationalActivity](#)
- [OperationalAgent](#)
- [OperationalConstraint](#)
- [OperationalExchange](#)
- [OperationalPerformer](#)
- [Rule](#)
- [SubjectOfOperationalConstraint](#)

View Specifications::Operational::Traceability

Contains the diagrams that document the Operational Traceability Viewpoint.

View Specifications::Operational::Traceability::Operational Traceability

Stakeholders: PMs, Enterprise Architects, Business Architects.

Concerns: traceability between capabilities and operational activities and capabilities and operational agents.

Definition: describes the mapping between the capabilities required by an Enterprise and the supporting operational

activities and operational agents.

Recommended Implementation: matrix format, SysML Block Definition Diagram.




Figure 8:17 - Operational Traceability

Elements

- [Capability](#)
- [CapableElement](#)
- [Exhibits](#)
- [MapsToCapability](#)
- [OperationalActivity](#)
- [OperationalAgent](#)
- [OperationalArchitecture](#)
- [OperationalPerformer](#)
- [Process](#)

8.1.4 View Specifications::Services

Stakeholders: Enterprise Architects, Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: specifications of services required to exhibit a Capability.

Definition: shows Service Specifications and required and provided service levels of these specifications required to exhibit a Capability or to support an Operational Activity.

View Specifications::Services::Taxonomy

Contains the diagrams that document the Services Taxonomy Viewpoint.

View Specifications::Services::Taxonomy::Services Taxonomy

Stakeholders: Enterprise Architects, Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: service specification types and required and provided service levels of these types.

Definition: shows the taxonomy of types of services and the level of service that they are expected to provide or are required to meet through the display of ActualMeasurements associated with the Provided and Required Service Level.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:18 - Services Taxonomy

Elements

- [ActualMeasurement](#)
- [ActualMeasurementSet](#)
- [ActualService](#)
- [Measurement](#)
- [PropertySet](#)
- [ProvidedServiceLevel](#)
- [RequiredServiceLevel](#)
- [ServicePolicy](#)
- [ServiceSpecification](#)
- [ServiceSpecificationGeneralization](#)

View Specifications::Services::Structure

Contains the diagrams that document the Services Structure Viewpoint.

View Specifications::Services::Structure::Services Structure

Stakeholders: Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: combination of services required to exhibit a capability.

Definition: shows the composition of services and how services are combined into a higher level service required to exhibit a capability or support an operational activity.

Recommended Implementation: SysML Block Definition Diagram, SysML Internal Block Diagram.




Figure 8:19 - Services Structure

Elements

- [InformationElement](#)
- [Measurement](#)
- [OperationalExchangeItem](#)
- [PropertySet](#)
- [ServiceConnector](#)
- [ServiceInterface](#)
- [ServiceMethod](#)
- [ServiceParameter](#)
- [ServicePort](#)
- [ServiceSpecification](#)
- [ServiceSpecificationRole](#)

View Specifications::Services::Connectivity

Contains the diagrams that document the Services Connectivity Viewpoint.

View Specifications::Services::Connectivity::Services Connectivity

Stakeholders: Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: interoperability among services

Definition: specifies service interfaces, e.g., provided and required service operations, to ensure compatibility and reusability of services.

Recommended Implementation: SysML Block Definition Diagram, SysML Internal Block Diagram, tabular format.




Figure 8:20 - Services Connectivity

Elements

- [ServiceConnector](#)
- [ServiceInterface](#)
- [ServiceMethod](#)
- [ServiceParameter](#)
- [ServicePort](#)
- [ServiceSpecification](#)
- [ServiceSpecificationRole](#)

View Specifications::Services::Processes

Contains the diagrams that document the Services Processes Viewpoint.

View Specifications::Services::Processes::Services Processes

Stakeholders: Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: the behavior of a service in terms of the operational activities it is expected to support.

Definition: provides detailed information regarding the allocation of service functions to service specifications, and data flows between service functions.

Recommended Implementation: SysML Activity Diagram, SysML Block Definition Diagram.




Figure 8:21 - Services Processes

Elements

- [IsCapableToPerform](#)
- [Process](#)
- [ProcessEdge](#)
- [ProcessOperation](#)
- [ProcessParameter](#)
- [ProcessUsage](#)
- [ServiceFunction](#)
- [ServiceFunctionAction](#)
- [ServiceFunctionEdge](#)
- [ServiceMethod](#)
- [ServiceParameter](#)
- [ServiceSpecification](#)
- UML2.5Metamodel::Activity
- UML2.5Metamodel::ActivityEdge
- UML2.5Metamodel::CallBehaviorAction
- UML2.5Metamodel::Operation
- UML2.5Metamodel::Parameter

View Specifications::Services::Processes::Services Processes BPMN Semantics

Stakeholders: Solution Providers, Software Architects, Business Architects.

Concerns: the behavior of a service in terms of the operational activities it is expected to support.

Definition: provides detailed information regarding the allocation of service functions to service specifications, and data flows between service functions using BPMN.

Recommended Implementation: BPMN Process Diagram, SysML Block Definition Diagram.




Figure 8:22 - Services Processes BPMN Semantics

Elements

- BPMN2Metamodel::CallActivity
- BPMN2Metamodel::Process
- BPMN2Metamodel::ResourceRole
- BPMN2Metamodel::SequenceFlow
- [InteractionRole](#)
- [IsCapableToPerform](#)
- [PerformsInContext](#)
- [Process](#)
- [ProcessEdge](#)
- [ProcessOperation](#)
- [ProcessUsage](#)
- [ServiceFunction](#)
- [ServiceFunctionAction](#)
- [ServiceFunctionEdge](#)
- [ServiceMethod](#)
- [ServiceParameter](#)
- [ServiceSpecification](#)
- [ServiceSpecificationRole](#)

View Specifications::Services::States

Contains the diagrams that document the Services States Viewpoint.

View Specifications::Services::States::Services States

Stakeholders: Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: the behavior of a service specification in terms of states and events causing transitions between states.

Definition: specifies the possible states a service specification may have, and the possible transitions between those states.

Recommended Implementation: SysML State Machine Diagram.




Figure 8:23 - Services States

Elements

- [ServiceSpecification](#)
- [ServiceStateDescription](#)
- [StateDescription](#)
- UML2.5Metamodel::StateMachine

View Specifications::Services::Interaction Scenarios

Contains the diagrams that document the Services Interaction Scenarios Viewpoint.

View Specifications::Services::Interaction Scenarios::Services Interaction Scenarios

Stakeholders: Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: the behavior of a service specification in terms of expected time-ordered examination of the interactions between service roles.

Definition: specifies how a service roles interact with each other, service providers and consumers, and the sequence and dependencies of those interactions.

Recommended Implementation: SysML Sequence Diagram.




Figure 8:24 - Services Interaction Scenarios

Elements

- [InteractionMessage](#)
- [InteractionRole](#)
- [InteractionScenario](#)
- [ServiceFunction](#)
- [ServiceInteractionScenario](#)
- [ServiceMessage](#)
- [ServiceMethod](#)
- [ServiceSpecification](#)
- [ServiceSpecificationRole](#)
- UML2.5Metamodel::Interaction
- UML2.5Metamodel::Lifeline
- UML2.5Metamodel::Message

View Specifications::Services::Constraints

Contains the diagrams that document the Services Constraints Viewpoint.

View Specifications::Services::Constraints::Services Constraints

Stakeholders: Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: service policies that apply to implementations of service specifications.

Definition: specifies traditional textual service policies that are constraints on the way that service specifications are implemented within resources. The addition of SysML parametrics provide a computational means of defining service policies across the enterprise or within a specific service configuration.

Recommended Implementation: tabular format, SysML Parametric Diagram.



Figure 8:25 - Services Constraints

Elements

- [Rule](#)
- [ServicePolicy](#)
- [ServiceSpecification](#)

View Specifications::Services::Roadmap

Contains the diagrams that document the Services Roadmap Viewpoint.

View Specifications::Services::Roadmap::Services Roadmap

Stakeholders: Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: service specification changes over time.

Definition: provides an overview of how a service specification changes over time. It shows the combination of several service specifications mapped against a timeline.

Recommended Implementation: timeline, SysML Block Definition Diagram, SysML Internal Block Diagram.




Figure 8:26 - Services Roadmap

Elements

- [ActualProject](#)
- [ActualProjectMilestone](#)
- [MilestoneDependency](#)
- [ServiceSpecification](#)

- [VersionedElement](#)
- [VersionOfConfiguration](#)
- [VersionSuccession](#)
- [WholeLifeConfiguration](#)

View Specifications::Services::Traceability

Contains the diagrams that document the Services Traceability Viewpoint.

View Specifications::Services::Traceability::Services Traceability

Stakeholders: Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: traceability between operational activities and service specifications that support them.

Definition: depicts the mapping of service specifications to operational activities and how service specifications contribute to the achievement of a capability.

Recommended Implementation: tabular or matrix format.




Figure 8:27 - Services Traceability

Elements

- [ActualService](#)
- [Capability](#)
- [CapableElement](#)
- [Consumes](#)
- [Exhibits](#)
- [OperationalActivity](#)
- [ServiceSpecification](#)

8.1.5 View Specifications::Personnel

Stakeholders: Human resources, Solution Providers, PMs.

Concerns: human factors.

Definition: aims to clarify the role of Human Factors (HF) when creating architectures in order to facilitate both Human Factors Integration (HFI) and systems engineering (SE).

View Specifications::Personnel::Taxonomy

Contains the diagrams that document the Personnel Taxonomy Viewpoint.

View Specifications::Personnel::Taxonomy::Personnel Taxonomy

Stakeholders: Human resources, Solution Providers, PMs.

Concerns: organizational resource types.

Definition: shows the taxonomy of types of organizational resources.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:28 - Personnel Taxonomy

Elements

- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [ResourcePerformer](#)
- [Responsibility](#)

View Specifications::Personnel::Structure

Contains the diagrams that document the Personnel Structure Viewpoint.

View Specifications::Personnel::Structure::Personnel Structure

Stakeholders: Human resources, Solution Providers, PMs.

Concerns: typical organizational structure used to support a capability(ies).

Definition: shows organizational structures and possible interactions between organizational resources.

Recommended Implementation: SysML Block Definition Diagram, SysML Internal Block Diagram.




Figure 8:29 - Personnel Structure

Elements

- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [PostRole](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- [Responsibility](#)
- [SubOrganization](#)

View Specifications::Personnel::Connectivity

Contains the diagrams that document the Personnel Connectivity Viewpoint.

View Specifications::Personnel::Connectivity::Personnel Connectivity

Stakeholders: Solution providers.

Concerns: interaction of organizational resources.

Definition: captures the possible interactions between organizational resources, including command and control relationships. Interactions typically illustrate the fundamental roles and management responsibilities.

Recommended Implementation: tabular format.




Figure 8:30 - Personnel Connectivity

Elements

- [Command](#)
- [Control](#)
- [DataElement](#)
- [Environment](#)
- [Exchange](#)
- [Function](#)
- [IsCapableToPerform](#)
- [MeasurableElement](#)
- [MeasurementSet](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [PropertySet](#)
- [Resource](#)
- [ResourceConnector](#)
- [ResourceExchange](#)
- [ResourceExchangeItem](#)
- [ResourceInterface](#)
- [ResourcePerformer](#)
- [ResourcePort](#)
- [ResourceRole](#)

- [Responsibility](#)

View Specifications::Personnel::Processes

Contains the diagrams that document the Personnel Processes Viewpoint.

View Specifications::Personnel::Processes::Personnel Processes

Stakeholders: Systems engineers, Solution providers.

Concerns: functions that have to be carried out by organizational resources.

Definition: specifies organizational resource functions in relation to resource definitions.

Recommended Implementation: SysML Activity Diagram, SysML Block Definition Diagram, BPMN Process Diagram as described in the Resources Processes section.




Figure 8:31 - Personnel Processes

Elements

- [ActivityPerformableUnderCondition](#)
- [ActualCondition](#)
- [DataElement](#)
- [Function](#)
- [FunctionAction](#)
- [FunctionEdge](#)
- [IsCapableToPerform](#)
- [Organization](#)

- [OrganizationalResource](#)
- [PerformsInContext](#)
- [PhysicalResource](#)
- [Post](#)
- [Process](#)
- [ProcessEdge](#)
- [ProcessOperation](#)
- [ProcessParameter](#)
- [ProcessUsage](#)
- [ResourceExchange](#)
- [ResourceExchangeItem](#)
- [ResourceMethod](#)
- [ResourceParameter](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- [Responsibility](#)
- UML2.5Metamodel::Activity
- UML2.5Metamodel::ActivityEdge
- UML2.5Metamodel::CallBehaviorAction
- UML2.5Metamodel::Operation
- UML2.5Metamodel::Parameter

View Specifications::Personnel::States

Contains the diagrams that document the Personnel States Viewpoint.

View Specifications::Personnel::States::Personnel States

Stakeholders: Systems Engineers, Software Engineers.

Concerns: capture state-based behavior of an organizational resource.

Definition: it is a graphical representation of states of an organizational resource and how that organizational resource responds to various events and actions.

Recommended Implementation: SysML State Machine Diagram.




Figure 8:32 - Personnel States

Elements

- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [ResourcePerformer](#)
- [ResourceStateDescription](#)
- [Responsibility](#)
- [StateDescription](#)
- UML2.5Metamodel::StateMachine

View Specifications::Personnel::Interaction Scenarios

Contains the diagrams that document the Personnel Interaction Scenarios Viewpoint.

View Specifications::Personnel::Interaction Scenarios::Personnel Interaction Scenarios

Stakeholders: Software Engineers, Systems Engineers.

Concerns: interactions between organizational resources (roles).

Definition: provides a time-ordered examination of the interactions between organizational resources.

Recommended Implementation: SysML Sequence Diagram, BPMN Collaboration Diagram.




Figure 8:33 - Personnel Interaction Scenarios

Elements

- [DataElement](#)
- [Function](#)
- [InteractionMessage](#)
- [InteractionRole](#)
- [InteractionScenario](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [Process](#)
- [ResourceExchange](#)
- [ResourceExchangeItem](#)
- [ResourceInteractionScenario](#)
- [ResourceMessage](#)
- [ResourceMethod](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- [Responsibility](#)
- UML2.5Metamodel::Interaction
- UML2.5Metamodel::Lifeline
- UML2.5Metamodel::Message

View Specifications::Personnel::Constraints

Contains the diagrams that document the Personnel Constraints Viewpoint.

View Specifications::Personnel::Constraints::Personnel Constraints: Competence

Stakeholders: Systems engineers, Solution providers.

Concerns: allocation of competencies to actual posts.

Definition: specifies requirements for actual organizational resources – by linking competencies and actual posts.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:34 - Personnel Constraints: Competence

Elements

- [ActualOrganization](#)
- [ActualOrganizationalResource](#)
- [ActualPerson](#)
- [ActualPost](#)
- [ActualResponsibility](#)
- [ActualResponsibleResource](#)
- [Competence](#)
- [CompetenceForRole](#)
- [CompetenceToConduct](#)
- [Function](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [ProvidesCompetence](#)
- [RequiresCompetence](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- [Responsibility](#)

View Specifications::Personnel::Constraints::Personnel Constraints: Drivers

Stakeholders: Systems engineers, Solution providers, Human resources.

Concerns: optimization of organizational resource behavior.

Definition: captures the factors that affect, constrain and characterize organizational resource behavior as the basis for

performance predictions at the level of actual persons and actual organizations. It creates a bridge between static architectural definitions and behavior predictions through executable models.

Recommended Implementation: tabular format, SysML Parametric Diagram, SysML Block Definition Diagram.




Figure 8:35 - Personnel Constraints: Drivers

Elements

- [ActualMeasurement](#)
- [ActualMeasurementSet](#)
- [Function](#)
- [IsCapableToPerform](#)
- [MeasurableElement](#)
- [Measurement](#)
- [MeasurementSet](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [Process](#)
- [ResourceConstraint](#)
- [ResourcePerformer](#)
- [Responsibility](#)
- [Rule](#)
- [SubjectOfResourceConstraint](#)

View Specifications::Personnel::Constraints::Personnel Constraints: Performance

Stakeholders: Human resources, solution providers.

Concerns: how well an actual organizational resource matches the needs of the actual organization.

Definition: provides a repository for human-related measures (i.e., quality objectives and performance criteria (HFI values)), targets and competences.
 Recommended Implementation: SysML Block Definition Diagram.




Figure 8:36 - Personnel Constraints: Performance

Elements

- [ActivityPerformableUnderCondition](#)
- [ActualCondition](#)
- [ActualMeasurement](#)
- [ActualMeasurementSet](#)
- [ActualOrganizationalResource](#)
- [ActualPerson](#)
- [ActualPost](#)
- [ActualPropertySet](#)
- [ActualResource](#)
- [ActualResponsibleResource](#)
- [ActualState](#)
- [DesiredEffect](#)
- [Desirer](#)
- [Function](#)
- [IsCapableToPerform](#)
- [MeasurableElement](#)
- [Measurement](#)
- [MeasurementSet](#)

- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
 - [Post](#)
 - [Process](#)
 - [ResourcePerformer](#)
 - [Responsibility](#)

View Specifications::Personnel::Roadmap

Contains the diagrams that document the Personnel Roadmap Viewpoint.

View Specifications::Personnel::Roadmap::Personnel Roadmap: Availability

Stakeholders: Human Resources, Training, Logisticians, Solution Providers.

Concerns: the staffing and training of resources.

Definition: defines the requirements and functions to ensure that actual persons with the right competencies, and in the right numbers, are available to fulfill actual posts.

Recommended Implementation: Timeline, SysML Block Definition Diagram.




Figure 8:37 - Personnel Roadmap: Availability

Elements

- [ActualMeasurement](#)
- [ActualOrganizationalResource](#)
- [ActualPerson](#)
- [ActualPost](#)
- [ActualProject](#)
- [ActualProjectMilestone](#)
- [ActualPropertySet](#)
- [ActualResource](#)
- [ActualResponsibleResource](#)
- [ActualState](#)
- [Asset](#)
- [FillsPost](#)
- [Measurement](#)
- [OrganizationalResource](#)

- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [Project](#)
- [ProjectMilestone](#)
- [PropertySet](#)
- [ResourceAsset](#)
- [ResourcePerformer](#)

View Specifications::Personnel::Roadmap::Personnel Roadmap: Evolution

Stakeholders: Human resources, Solution Providers.

Concerns: organizational structure changes over time.

Definition: provides an overview of how an organizational structure changes over time. It shows the structure of several organizational structures mapped against a timeline.

Recommended Implementation: timeline, SysML Block Definition Diagram, SysML Internal Block Diagram.




Figure 8:38 - Personnel Roadmap: Evolution

Elements

- [ActualProject](#)
- [ActualProjectMilestone](#)
- [MilestoneDependency](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [ResourcePerformer](#)
- [Responsibility](#)
- [VersionedElement](#)
- [VersionOfConfiguration](#)
- [VersionSuccession](#)

- [WholeLifeConfiguration](#)

View Specifications::Personnel::Roadmap::Personnel Roadmap: Forecast

Stakeholders: Human resources, Logisticians, Solution Providers.

Concerns: competencies and skills forecast.

Definition: defines the underlying current and expected supporting competencies and skills of organizational resources.

Recommended Implementation: timeline, tabular format, SysML Block Definition Diagram.




Figure 8:39 - Personnel Roadmap: Forecast

Elements

- [ActualEnterprisePhase](#)
- [ActualPropertySet](#)
- [ActualState](#)
- [Asset](#)
- [Competence](#)
- [Forecast](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [ResourcePerformer](#)
- [Responsibility](#)
- [SubjectOfForecast](#)

View Specifications::Personnel::Traceability

Contains the diagrams that document the Personnel Traceability Viewpoint.

View Specifications::Personnel::Traceability::Personnel Traceability

Stakeholders: Systems Engineers, Enterprise Architects, Solution Providers, Business Architects.

Concerns: traceability between operational activities and functions that implements them.

Definition: depicts the mapping of functions (performed by organizational resources) to operational activities and thus identifies the transformation of an operational need into a purposeful function performed by an organizational resource or solution.

Recommended Implementation: Matrix format, SysML Block Definition Diagram.




Figure 8:40 - Personnel Traceability

Elements

- [Function](#)
- [Implements](#)
- [OperationalActivity](#)
- [ServiceFunction](#)

8.1.6 View Specifications::Resources

Stakeholders: Systems Engineers, Resource Owners, Implementers, Solution Providers, IT Architects.

Concerns: definition of solution architectures to implement operational requirements.

Definition: captures a solution architecture consisting of resources, e.g., organizational, software, artifacts, capability configurations, natural resources that implement the operational requirements. Further design of a resource is typically detailed in SysML or UML.

View Specifications::Resources::Taxonomy

Contains the diagrams that document the Resources Taxonomy Viewpoint.

View Specifications::Resources::Taxonomy::Resources Taxonomy

Stakeholders: Solution Providers, Systems Engineers, IT Architects, Implementers.

Concerns: resource types.

Definition: shows the taxonomy of types of resources.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:41 - Resources Taxonomy

Elements

- [Asset](#)
- [CapabilityConfiguration](#)
- [Implements](#)
- [Measurement](#)
- [NaturalResource](#)
- [OperationalAgent](#)
- [OperationalPerformer](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [PropertySet](#)
- [PropertySetGeneralization](#)
- [ResourceArchitecture](#)
- [ResourceArtifact](#)
- [ResourceAsset](#)
- [ResourceExchange](#)
- [ResourceMitigation](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- [Responsibility](#)
- [Software](#)
- [System](#)

View Specifications::Resources::Structure

Contains the diagrams that document the Resources Structure Viewpoint.

View Specifications::Resources::Structure::Resources Structure

Stakeholders: Systems Engineers, Resource Owners, Implementers, Solution Providers.

Concerns: reference the resource structure, connectors and interfaces in a specific context.

Definition: defines the physical resources, e.g., capability configuration(s)/system(s) and interactions necessary to implement a specific set of Operational Performer(s). Can be used to represent communications networks and pathways that link communications resources and provides details regarding their configuration.

Recommended Implementation: SysML Internal Block Diagram, SysML Block Definition Diagram.




Figure 8:42 - Resources Structure

Elements

- [Asset](#)
- [CapabilityConfiguration](#)
- [Measurement](#)
- [NaturalResource](#)
- [PhysicalResource](#)
- [PropertySet](#)
- [Protocol](#)
- [ProtocolImplementation](#)
- [ResourceArchitecture](#)
- [ResourceArtifact](#)
- [ResourceAsset](#)
- [ResourceConnector](#)
- [ResourceExchange](#)
- [ResourceInterface](#)
- [ResourceMitigation](#)
- [ResourcePerformer](#)
- [ResourcePort](#)

- [ResourceRole](#)
- [Software](#)

View Specifications::Resources::Connectivity

Contains the diagrams that document the Resources Connectivity Viewpoint.

View Specifications::Resources::Connectivity::Resources Connectivity

Stakeholders: Systems Engineers, IT Architects, Solution Providers, Implementers.

Concerns: capture the interactions between resources.

Definition: summarizes interactions between resources of information, systems, personnel, natural resources etc. and the functions that produce and consume them. Measurements can optionally be included.

Recommended Implementation: SysML Internal Block Diagram, tabular format.




Figure 8:43 - Resources Connectivity

Elements

- [CapabilityConfiguration](#)
- [DataElement](#)
- [Exchange](#)
- [Function](#)
- [FunctionAction](#)
- [FunctionEdge](#)
- [GeoPoliticalExtentType](#)
- [IsCapableToPerform](#)

- [MeasurableElement](#)
- [Measurement](#)
- [MeasurementSet](#)
- [NaturalResource](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [Process](#)
- [PropertySet](#)
- [Resource](#)
- [ResourceArchitecture](#)
- [ResourceArtifact](#)
- [ResourceConnector](#)
- [ResourceExchange](#)
- [ResourceExchangeItem](#)
- [ResourceInterface](#)
- [ResourceMitigation](#)
- [ResourcePerformer](#)
- [ResourcePort](#)
- [ResourceRole](#)
- [ResourceSignal](#)
- [Software](#)
- [Technology](#)

View Specifications::Resources::Processes

Contains the diagrams that document the Resources Processes Viewpoint.

View Specifications::Resources::Processes::Resources Processes

Stakeholders: Solution Providers, Systems Engineers, IT Architects.

Concerns: captures activity based behavior and flows.

Definition: describes the functions that are normally conducted in the course of implementing operational activity(ies) in support of capability(ies). It describes the functions, their Inputs/Outputs, function actions and flows between them.

Recommended Implementation: SysML Activity Diagram, SysML Block Definition Diagram.




Figure 8:44 - Resources Processes

Elements

- [ActivityPerformableUnderCondition](#)
- [ActualCondition](#)
- [DataElement](#)
- [Function](#)
- [FunctionAction](#)
- [FunctionEdge](#)
- [Implements](#)
- [OperationalActivity](#)
- [PerformsInContext](#)
- [PhysicalResource](#)
- [Process](#)
- [ProcessEdge](#)
- [ProcessParameter](#)
- [ProcessUsage](#)
- [ResourceArchitecture](#)
- [ResourceExchange](#)
- [ResourceExchangeItem](#)
- [ResourceParameter](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- UML2.5Metamodel::Activity
- UML2.5Metamodel::ActivityEdge
- UML2.5Metamodel::CallBehaviorAction
- UML2.5Metamodel::Parameter

View Specifications::Resources::Processes::Resources Processes BPMN Semantics

Stakeholders: Solution Providers, IT Architects.

Concerns: captures activity based behavior and flows using BPMN.

Definition: describes the functions that are normally conducted in the course of implementing operational activity(ies) in support of capability(ies). It describes the functions, their Inputs/Outputs, function actions and flows between them using BPMN.

Recommended Implementation: BPMN Process Diagram.




Figure 8:45 - Resources Processes BPMN Semantics

Elements

- [ActivityPerformableUnderCondition](#)
- [AssetRole](#)
- BPMN2Metamodel::BPMNMessage
- BPMN2Metamodel::CallActivity
- BPMN2Metamodel::MessageFlow
- BPMN2Metamodel::Process
- BPMN2Metamodel::ResourceRole
- BPMN2Metamodel::SequenceFlow
- [DataElement](#)

- [Exchange](#)
- [ExchangeItem](#)
- [Function](#)
- [FunctionAction](#)
- [FunctionEdge](#)
- [Implements](#)
- [OperationalActivity](#)
- [PerformsInContext](#)
- [PhysicalResource](#)
- [Process](#)
- [ProcessEdge](#)
- [ProcessUsage](#)
- [ResourceArchitecture](#)
- [ResourceExchange](#)
- [ResourceExchangeItem](#)
- [ResourceParameter](#)
- [ResourcePerformer](#)
- [ResourceRole](#)

View Specifications::Resources::States

Contains the diagrams that document the Resources States Viewpoint.

View Specifications::Resources::States::Resources States

Stakeholders: Systems Engineers, Software Engineers.

Concerns: capture state-based behavior of a resource.

Definition: it is a graphical representation of states of a resource and how that resource responds to various events and actions.

Recommended Implementation: SysML State Machine Diagram.




Figure 8:46 - Resources States

Elements

- [ResourcePerformer](#)
- [ResourceStateDescription](#)
- [StateDescription](#)
- UML2.5Metamodel::StateMachine

View Specifications::Resources::Interaction Scenarios

Contains the diagrams that document the Resources Interaction Scenarios Viewpoint.

View Specifications::Resources::Interaction Scenarios::Resources Interaction Scenarios

Stakeholders: Software Engineers, Systems Engineers.

Concerns: interactions between resources (roles).

Definition: provides a time-ordered examination of the interactions between resources.

Recommended Implementation: SysML Sequence Diagram.




Figure 8:47 - Resources Interaction Scenarios

Elements

- [Function](#)
- [InteractionMessage](#)
- [InteractionRole](#)
- [InteractionScenario](#)
- [ResourceExchange](#)
- [ResourceInteractionScenario](#)
- [ResourceMessage](#)
- [ResourceMethod](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- UML2.5Metamodel::Interaction
- UML2.5Metamodel::Lifeline
- UML2.5Metamodel::Message

View Specifications::Resources::Constraints

Contains the diagrams that document the Resources Constraints Viewpoint.

View Specifications::Resources::Constraints::Resources Constraints

Stakeholders: Systems Engineers, IT Architects, Solution Providers, Implementers.

Concerns: define limitations, constraints and performance parameters for resources, their interactions, performed functions, and data.

Definition: specifies traditional textual rules/non-functional requirements that are constraints on resources, their interactions, performed functions, and data. The addition of SysML parametrics provide a computational means of defining resource constraints within a specific context.

Recommended Implementation: tabular format, SysML Block Definition Diagram, SysML Parametric Diagram, OCL.




Figure 8:48 - Resources Constraints

Elements

- [ActualResource](#)
- [CapabilityConfiguration](#)
- [DataElement](#)
- [Function](#)
- [NaturalResource](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [ResourceArchitecture](#)
- [ResourceArtifact](#)
- [ResourceConstraint](#)
- [ResourcePerformer](#)
- [ResourceRole](#)

- [Responsibility](#)
- [Rule](#)
- [SubjectOfResourceConstraint](#)

View Specifications::Resources::Roadmap

Contains the diagrams that document the Resources Roadmap Viewpoint.

View Specifications::Resources::Roadmap::Resources Roadmap: Evolution

Stakeholders: Systems Engineers, IT Architects, Solution Providers, Implements.

Concerns: resource structure changes over time.

Definition: provides an overview of how a resource structure changes over time. It shows the structure of several resources mapped against a timeline.

Recommended Implementation: timeline, SysML Block Definition Diagram, SysML Internal Block Diagram.




Figure 8:49 - Resources Roadmap: Evolution

Elements

- [ActualProject](#)
- [ActualProjectMilestone](#)
- [MilestoneDependency](#)
- [ResourcePerformer](#)
- [VersionedElement](#)
- [VersionOfConfiguration](#)
- [VersionSuccession](#)
- [WholeLifeConfiguration](#)

View Specifications::Resources::Roadmap::Resources Roadmap: Forecast

Stakeholders: Solution Providers, Systems Engineers, IT Architects.

Concerns: technology forecast.

Definition: defines the underlying current and expected supporting technologies. Expected supporting technologies are those that can be reasonably forecast given the current state of technology, and expected improvements / trends.

Recommended Implementation: timeline, tabular format, SysML Block Definition Diagram.




Figure 8:50 - Resources Roadmap: Forecast

Elements

- [ActualEnterprisePhase](#)
- [ActualPropertySet](#)
- [ActualState](#)
- [CapabilityConfiguration](#)
- [Forecast](#)
- [NaturalResource](#)
- [PhysicalResource](#)
- [ResourceArchitecture](#)
- [ResourceArtifact](#)
- [ResourceMitigation](#)
- [ResourcePerformer](#)
- [Software](#)
- [SubjectOfForecast](#)
- [Technology](#)

View Specifications::Resources::Traceability

Contains the diagrams that document the Resources Traceability Viewpoint.

View Specifications::Resources::Traceability::Resources Traceability

Stakeholders: Systems Engineers, Enterprise Architects, Solution Providers, Business Architects.

Concerns: traceability between operational activities and functions that implements them.

Definition: depicts the mapping of functions to operational activities and thus identifies the transformation of an operational need into a purposeful function performed by a resource or solution.

Recommended Implementation: Matrix format, SysML Block Definition Diagram.




Figure 8:51 - Resources Traceability

Elements

- [Capability](#)
- [CapableElement](#)
- [Exhibits](#)
- [Function](#)
- [Implements](#)
- [IsCapableToPerform](#)
- [OperationalActivity](#)
- [OperationalAgent](#)
- [ResourcePerformer](#)
- [ServiceFunction](#)

8.1.7 View Specifications::Security

Stakeholders: Security Architects, Security Engineers, Systems Engineers, Operational Architects.

Concerns: addresses the security constraints and information assurance attributes that exist on exchanges between resources and OperationalPerformers

Definition: illustrates the security assets, security constraints, security controls, families, and measures required to address specific security concerns.

View Specifications::Security::Taxonomy

Contains the diagrams that document the Security Taxonomy Viewpoint.

View Specifications::Security::Taxonomy::Security Taxonomy

Stakeholders: Security Architects, Security Engineers.

Concerns: Security assets and security enclaves.

Definition: Defines the hierarchy of security assets and asset owners that are available to implement security, security constraints (policy, guidance, laws and regulations) and details where they are located (security enclaves).

Recommended Implementation: tabular format, SysML Block Definition Diagram.




Figure 8:52 - Security Taxonomy

Elements

- [ActualLocation](#)
- [Asset](#)
- [DataElement](#)
- [InformationElement](#)
- [LocationHolder](#)
- [Measurement](#)
- [MeasurementSet](#)
- [OperationalAgent](#)
- [OperationalArchitecture](#)
- [OperationalMitigation](#)
- [OperationalPerformer](#)
- [PropertySet](#)
- [ResourceArchitecture](#)
- [ResourceAsset](#)
- [ResourceMitigation](#)
- [ResourcePerformer](#)

- [Risk](#)
- [SecurityAvailability](#)
- [SecurityCategory](#)
- [SecurityClassification](#)
- [SecurityClassificationKind](#)
- [SecurityEnclave](#)
- [SecurityIntegrity](#)
- [SecurityMeasurement](#)

View Specifications::Security::Structure

Contains the diagrams that document the Security Structure Viewpoint.

View Specifications::Security::Structure::Security Structure

Stakeholders: Security Architects, Security Engineers.

Concerns: The structure of security information and where it is used at the operational and resource level.

Definition: Captures the allocation of assets (operational and resource, information and data) across the security enclaves, shows applicable security controls necessary to protect organizations, systems and information during processing, while in storage (bdd), and during transmission (flows on an ibd). This view also captures Asset Aggregation and allocates the usage of the aggregated information at a location through the use of the SecurityProperty.

Recommended Implementation: SysML Internal Block Diagram, SysML Block Definition Diagram.




Figure 8:53 - Security Structure

Elements

- [Asset](#)
- [DataElement](#)
- [DataRole](#)
- [InformationElement](#)
- [InformationRole](#)
- [OperationalAgent](#)
- [OperationalAsset](#)
- [OperationalConnector](#)
- [OperationalExchange](#)

- [OperationalPerformer](#)
- [OperationalPort](#)
- [OperationalRole](#)
- [ResourceAsset](#)
- [ResourceConnector](#)
- [ResourceExchange](#)
- [ResourcePerformer](#)
- [ResourcePort](#)
- [ResourceRole](#)
- [SecurityCategory](#)

View Specifications::Security::Connectivity

Contains the diagrams that document the Security Connectivity Viewpoint.

View Specifications::Security::Connectivity::Security Connectivity

Stakeholders: Security Architects, Security Engineers.

Concerns: Addresses the security constraints and information assurance attributes that exist on exchanges across resources and across performers.

Definition: Lists security exchanges across security assets; the applicable security controls; and the security enclaves that house the producers and consumers of the exchanges. Measurements can optionally be included.

Recommended Implementation: SysML Internal Block Diagram, tabular format.




Figure 8:54 - Security Connectivity

Elements

- [Caveat](#)
- [MeasurableElement](#)
- [MeasurementSet](#)
- [OperationalAgent](#)
- [OperationalConnector](#)
- [OperationalExchange](#)
- [OperationalExchangeItem](#)
- [OperationalInterface](#)
- [OperationalPerformer](#)
- [OperationalPort](#)
- [OperationalRole](#)
- [ResourceConnector](#)
- [ResourceExchange](#)
- [ResourceExchangeItem](#)
- [ResourceInterface](#)
- [ResourcePerformer](#)
- [ResourcePort](#)
- [ResourceRole](#)
- [SecurityConstraint](#)
- [SubjectOfSecurityConstraint](#)

View Specifications::Security::Processes

Contains the diagrams that document the Security Processes Viewpoint.

View Specifications::Security::Processes::Security Processes

Stakeholders: Security Architects, Security Engineers.

Concerns: The specification of the Security Control families, security controls, and measures required to address a specific security baseline.

Definition: Provides a set of Security Controls and any possible enhancements as applicable to assets. The activity diagram describes operational or resource level processes that apply (operational level) or implement (resource level) security controls/enhancements to assets located in enclaves and across enclaves. This Security Process view can be instantiated either as a variant of an activity/flow diagram or as a hierarchical work breakdown structure.

Recommended Implementation: SysML Activity Diagram, SysML Block Definition Diagram, BPMN Process Diagram as described in Operational Processes and Resources Processes sections.




Figure 8:55 - Security Processes

Elements

- [Function](#)
- [FunctionAction](#)
- [IsCapableToPerform](#)
- [MeasurableElement](#)
- [MeasurementSet](#)
- [OperationalActivity](#)
- [OperationalActivityAction](#)
- [OperationalAgent](#)
- [OperationalRole](#)
- [PerformsInContext](#)
- [Process](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- [SecurityProcess](#)
- [SecurityProcessAction](#)

View Specifications::Security::Constraints

Contains the diagrams that document the Security Constraints Viewpoint.

View Specifications::Security::Constraints::Security Constraints

Stakeholders: Security Architects, Security Engineers, Risk Analysts.

Concerns: (i) Security-related policy, guidance, laws and regulations as applicable to assets, (ii) threats, vulnerabilities, and risk assessments as applicable to assets.

Definition: (i) Specifies textual rules/non-functional requirements that are security constraints on resources, information and data (e.g. security-related in the form of rules (e.g. access control policy)). A common way of representing access control policy is through the use of XACML (eXtensible Access Control Markup Language), it is expected that implementations of UAF allow users to link security constraints to external files represented in XACML. (ii) Identifies risks, specifies risk likelihood, impact, asset criticality, other measurements and enables risk assessment.

Recommended Implementation: tabular or Matrix format, SysML Block Definition Diagram, SysML Parametric Diagram, or OCL.




Figure 8:56 - Security Constraints

Elements

- [ActualMeasurement](#)
- [ActualPropertySet](#)
- [ActualResource](#)

- [ActualResponsibleResource](#)
- [ActualRisk](#)
- [Affects](#)
- [AffectsInContext](#)
- [Asset](#)
- [AssetRole](#)
- [EnhancedSecurityControl](#)
- [Enhances](#)
- [Measurement](#)
- [Mitigates](#)
- [OperationalAgent](#)
- [OperationalRole](#)
- [OrganizationalResource](#)
- [OwnsRisk](#)
- [OwnsRiskInContext](#)
- [PropertySet](#)
- [Protects](#)
- [ProtectsInContext](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- [Risk](#)
- [Rule](#)
- Satisfy
- [SecurityConstraint](#)
- [SecurityControl](#)
- [SecurityControlFamily](#)
- [SecurityProcess](#)
- [SubjectOfSecurityConstraint](#)

View Specifications::Security::Traceability

Contains the diagrams that document the Security Traceability Viewpoint.

View Specifications::Security::Traceability::Security Traceability

Stakeholders: Security Architects, Security Engineers, Risk Analysts.

Concerns: traceability between risk and risk owner, risk mitigations, and affected asset roles.

Definition: depicts the mapping of a risk to each of the following: risk owner, risk mitigations, and affected asset roles.

Recommended Implementation: Matrix format, SysML Block Definition Diagram.




Figure 8:57 - Security Traceability

Elements

- [Affects](#)
- [AffectsInContext](#)
- [Asset](#)
- [AssetRole](#)
- [DataRole](#)
- [InformationRole](#)
- [Mitigates](#)
- [OperationalRole](#)
- [OwnsRiskInContext](#)
- [Protects](#)
- [ProtectsInContext](#)
- [ResourceRole](#)
- [Risk](#)
- [Satisfy](#)
- [SecurityControl](#)

8.1.8 View Specifications::Projects

Stakeholders: PMs, Project Portfolio Managers, Enterprise Architects.

Concerns: project portfolio, projects and project milestones.

Definition: describes projects and project milestones, how those projects deliver capabilities, the organizations contributing to the projects and dependencies between projects.

View Specifications::Projects::Taxonomy

Contains the diagrams that document the Project Taxonomy Viewpoint.

View Specifications::Projects::Taxonomy::Project Taxonomy

Stakeholders: PMs, Project Portfolio Managers, Enterprise Architects. Concerns: types of projects and project milestones. Definition: shows the taxonomy of types of projects and project milestones. Recommended Implementation: SysML Block Definition Diagram.




Figure 8:58 - Project Taxonomy

Elements

- [ActualProject](#)
- [ActualProjectMilestone](#)
- [MilestoneDependency](#)
- [Project](#)
- [ProjectMilestone](#)
- [ProjectMilestoneRole](#)
- [ProjectSequence](#)

View Specifications::Projects::Structure

Contains the diagrams that document the Project Structure Viewpoint.

View Specifications::Projects::Structure::Project Structure

Stakeholders: PMs.

Concerns: relationships between types of projects and project milestones.

Definition: provides a template for an actual project(s) road map(s) to be implemented.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:59 - Project Structure

Elements

- [ActualOrganization](#)
- [ActualPost](#)
- [ActualProject](#)
- [ActualPropertySet](#)
- [ActualResponsibleResource](#)
- [ActualState](#)
- [Project](#)
- [ProjectMilestone](#)
- [ProjectMilestoneRole](#)
- [ProjectTheme](#)
- [ResourceRole](#)
- [ResponsibleFor](#)
- [StatusIndicators](#)

View Specifications::Projects::Connectivity

Contains the diagrams that document the Project Connectivity Viewpoint.

View Specifications::Projects::Connectivity::Project Connectivity

Stakeholders: PMs.

Concerns: relationships between projects and project milestones.

Definition: shows how projects and project milestones are related in sequence.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:60 - Project Connectivity

Elements

- [Project](#)
- [ProjectMilestone](#)
- [ProjectMilestoneRole](#)
- [ResourcePerformer](#)

View Specifications::Projects::Processes

Contains the diagrams that document the Project Processes Viewpoint.

View Specifications::Projects::Processes::Project Processes

Stakeholders: PMs.

Concerns: captures project tasks (ProjectActivities) and flows between them.

Definition: describes the ProjectActivities that are normally conducted in the course of projects to support capability(ies) and implement resources. It describes the ProjectActivities, their Inputs/Outputs, ProjectActivityActions and flows between them.

Recommended Implementation: SysML Activity Diagram, SysML Block Definition Diagram, BPMN Process Diagram as described in Resources Processes section.




Figure 8:61 - Project Processes

Elements

- [ActualProject](#)
- [DataElement](#)
- [Function](#)
- [FunctionAction](#)
- [FunctionEdge](#)
- [GeoPoliticalExtentType](#)
- [IsCapableToPerform](#)
- [Organization](#)
- [OrganizationalResource](#)
- [ProjectActivity](#)
- [ProjectActivityAction](#)
- [ResourceExchange](#)
- [ResourceExchangeItem](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- [ResourceSignal](#)

View Specifications::Projects::Roadmap

Contains the diagrams that document the Project Roadmap Viewpoint.

View Specifications::Projects::Roadmap::Project Roadmap

Stakeholders: PMs, Capability Owners, Solution Providers, Enterprise Architects.

Concerns: the product portfolio management; a planning of capability delivery.

Definition: provides a timeline perspective on programs or projects

Recommended Implementation: timeline, tabular format, SysML Block Definition Diagram.




Figure 8:62 - Project Roadmap

Elements

- [ActualProject](#)
- [ActualProjectMilestone](#)
- [ActualProjectMilestoneRole](#)
- [ActualPropertySet](#)
- [ActualResource](#)
- [ActualState](#)
- [CapabilityConfiguration](#)
- [FieldedCapability](#)
- [MilestoneDependency](#)
- [Project](#)
- [ProjectMilestone](#)
- [ProjectMilestoneRole](#)
- [ProjectSequence](#)
- [ProjectStatus](#)
- [ProjectTheme](#)
- [ResourceArchitecture](#)
- [ResourcePerformer](#)
- [StatusIndicators](#)

View Specifications::Projects::Traceability

Contains the diagrams that document the Project Traceability Viewpoint.

View Specifications::Projects::Traceability::Project Traceability

Stakeholders: PMs, Project Portfolio Managers, Enterprise Architects.

Concerns: traceability between capabilities and projects that deliver them.

Definition: depicts the mapping of projects to capabilities and thus identifies the transformation of a capability(ies) into a purposeful implementation via projects.

Recommended Implementation: Matrix format, SysML Block Definition Diagram.




Figure 8:63 - Project Traceability

Elements

- [ActualProject](#)
- [ActualProjectMilestone](#)
- [ActualResource](#)
- [Capability](#)
- [CapableElement](#)
- [Exhibits](#)
- [ResourcePerformer](#)

8.1.9 View Specifications::Standards

Stakeholders: Solution Providers, Systems Engineers, Software Engineers, Systems Architects, Business Architects.

Concerns: technical and non-technical Standards applicable to the architecture.

Definition: shows the technical, operational, and business Standards applicable to the architecture. Defines the underlying current and expected Standards.

View Specifications::Standards::Taxonomy

Contains the diagrams that document the Standards Taxonomy Viewpoint.

View Specifications::Standards::Taxonomy::Standards Taxonomy

Stakeholders: Solution Providers, Systems Engineers, Software Engineers, Systems Architects, Business Architects.

Concerns: technical and non-technical standards, guidance and policy applicable to the architecture.

Definition: shows the taxonomy of types of technical, operational, and business standards, guidance and policy applicable to the architecture.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:64 - Standards Taxonomy

Elements

- [ActualOrganization](#)
- [CapabilityConfiguration](#)
- [Protocol](#)
- [ProtocolStack](#)
- [ResourceArchitecture](#)
- [ResourcePerformer](#)
- [Standard](#)
- [StandardOperationalActivity](#)
- [UAFEElement](#)

View Specifications::Standards::Structure

Contains the diagrams that document the Standards Structure Viewpoint.

View Specifications::Standards::Structure::Standards Structure

Stakeholders: Solution Providers, Systems Engineers, Software Engineers, Systems Architects.
 Concerns: the specification of the protocol stack used in the architecture.
 Definition: shows the composition of standards required to achieve the architecture's objectives.
 Recommended Implementation: SysML Internal Block Diagram.




Figure 8:65 - Standards Structure

Elements

- [Protocol](#)
- [ProtocolLayer](#)
- [ProtocolStack](#)
- [Standard](#)

View Specifications::Standards::Roadmap

Contains the diagrams that document the Standards Roadmap Viewpoint.

View Specifications::Standards::Roadmap::Standards Roadmap

Stakeholders: Solution Providers, Systems Engineers, Systems Architects, Software Engineers, Business Architects.

Concerns: expected changes in technology-related standards and conventions, operational standards, or business standards and conventions.

Definition: defines the underlying current and expected standards. Expected standards are those that can be reasonably forecast given the current state of technology, and expected improvements / trends.

Recommended Implementation: timeline, tabular format, SysML Block Definition Diagram.




Figure 8:66 - Standards Roadmap

Elements

- [ActualEnterprisePhase](#)
- [Forecast](#)
- [Protocol](#)
- [Standard](#)
- [SubjectOfForecast](#)

View Specifications::Standards::Traceability

Contains the diagrams that document the Standards Traceability Viewpoint.

View Specifications::Standards::Traceability::Standards Traceability

Stakeholders: Solution Providers, Systems Engineers, Software Engineers, Systems Architects, Business Architects.

Concerns: standards that need to be taken in account to ensure the interoperability of the implementation of architectural elements.

Definition: shows the applicability of standards to specific elements in the architecture.

Recommended Implementation: tabular format, matrix format, SysML Block Definition Diagram.




Figure 8:67 - Standards Traceability

Elements

- [Protocol](#)
- [Standard](#)
- [UAFElement](#)

8.1.10 View Specifications::Actual Resources

Stakeholders: Solution Providers, Systems Engineers, Business Architects, Human Resources.

Concerns: the analysis, e.g., evaluation of different alternatives, what-if, trade-offs, V&V on the actual resource configurations.

Definition: illustrates the expected or achieved actual resource configurations and actual relationships between them.

View Specifications::Actual Resources::Structure

Contains the diagrams that document the Actual Resources Structure Viewpoint.

View Specifications::Actual Resources::Structure::Actual Resources Structure

Stakeholders: Solution Providers, Systems Engineers, Business Architects.

Concerns: the analysis, e.g., evaluation of different alternatives, what-if, trade-offs, V&V on the actual resource configurations as it provides a means to capture different solution architectures. The detailed analysis (trade-off, what-if etc.) is carried out using the Resource Constraints view.

Definition: illustrates the expected or achieved actual resource configurations required to meet an operational need.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:68 - Actual Resources Structure

Elements

- [ActualOrganization](#)
- [ActualOrganizationalResource](#)
- [ActualPerson](#)
- [ActualPost](#)
- [ActualResource](#)
- [ActualResponsibility](#)
- [ActualResponsibleResource](#)
- [CapabilityConfiguration](#)
- [FieldedCapability](#)
- [Organization](#)
- [Person](#)
- [Post](#)
- [ResourcePerformer](#)
- [Responsibility](#)

View Specifications::Actual Resources::Connectivity

Contains the diagrams that document the Actual Resources Connectivity Viewpoint.

View Specifications::Actual Resources::Connectivity::Actual Resources Connectivity

Stakeholders: Solution Providers, Systems Engineers, Business Architects.

Concerns: the communication of actual resource.

Definition: illustrates the actual resource configurations and actual relationships between them.

Recommended Implementation: tabular format, SysML Block Definition Diagram, SysML Internal Block Diagram, SysML Sequence Diagram.




Figure 8:69 - Actual Resources Connectivity

Elements

- [ActualOrganization](#)
- [ActualOrganizationalResource](#)
- [ActualPerson](#)
- [ActualPost](#)
- [ActualResource](#)
- [ActualResourceRelationship](#)
- [ActualResponsibility](#)
- [ActualResponsibleResource](#)
- [FieldedCapability](#)

View Specifications::Actual Resources::Traceability

Contains the diagrams that document the Actual Resources Traceability Viewpoint.

View Specifications::Actual Resources::Traceability::Actual Resources Traceability

Stakeholders: Systems Engineers, Enterprise Architects, Solution Providers, Business Architects.

Concerns: traceability between operational activities and functions that implements them.

Definition: depicts the mapping of functions to operational activities and thus identifies the transformation of an operational need into a purposeful function performed by a resource or solution.

Recommended Implementation: Matrix format, SysML Block Definition Diagram.




Figure 8:70 - Actual Resources Traceability

Elements

- [ActualResource](#)
- [Capability](#)
- [CapableElement](#)
- [Exhibits](#)

8.1.11 View Specifications::Dictionary

Stakeholders: Architects, users of the architecture, Capability Owners, Systems Engineers, Solution Providers.

Concerns: Definitions for all the elements in the architecture, libraries of environments and measurements.

Definition: Presents all the elements used in an architecture. Can be used specifically to capture:

- a. Elements and relationships that are involved in defining the environments applicable to capability, operational concept or set of systems.
- b. Measurable properties that can be used to support analysis such as KPIs, MoEs, TPIs etc.

View Specifications::Dictionary::Dictionary

Stakeholders: Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: provides a central reference for a given architecture’s data and metadata. It enables the set of architecture description to stand alone, with minimal reference to outside resources.

Definition: contains definitions of terms used in the given architecture. It consists of textual definitions in the form of a glossary, their taxonomies, and their metadata (i.e., data about architecture data), including metadata for any custom-tailored views. Architects should use standard terms where possible (i.e., terms from existing, approved dictionaries, glossaries, and lexicons).

Recommended Implementation: text, table format.




Figure 8:71 - Dictionary

Elements

- [Alias](#)
- [Definition](#)
- [Information](#)
- [SameAs](#)
- [UAFElement](#)

8.1.12 View Specifications::Summary & Overview

Stakeholders: Executives, PMs, Enterprise Architects.

Concerns: executive-level summary information in a consistent form.

Definition: provides executive-level summary information in a consistent form that allows quick reference and comparison between architectural descriptions. Includes assumptions, constraints, and limitations that may affect high-level decisions relating to an architecture-based work program.

View Specifications::Summary & Overview::Summary & Overview

Stakeholders: Decision makers, Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: quick overview of an architecture description and summary of analysis. In the initial phases of architecture development, it serves as a planning guide. Upon completion of an architecture, it provides a summary of findings, and any conducted analysis.

Definition: provides executive-level summary information in a consistent form that allows quick reference and comparison among architectures. The Summary and Overview includes assumptions, constraints, and limitations that may affect high-level decision processes involving the architecture.

Recommended Implementation: text, free form diagram, table format.




Figure 8:72 - Summary & Overview

Elements

- [ActualEnterprisePhase](#)
- [ActualOrganizationalResource](#)
- [ArchitecturalDescription](#)
- [ArchitecturalReference](#)
- [Architecture](#)
- [ArchitectureMetadata](#)
- [Concern](#)
- [EnterprisePhase](#)
- [Metadata](#)
- [OperationalArchitecture](#)
- [OrganizationalResource](#)
- [ResourceArchitecture](#)
- [Stakeholder](#)
- [View](#)
- [Viewpoint](#)
- [WholeLifeEnterprisePhase](#)

8.1.13 View Specifications::Requirements

Stakeholders: Requirement Engineers, Solution Providers, Systems Engineers, Software Engineers, Systems Architects, Business Architects.

Concerns: requirements traceability.

Definition: used to represent requirements, their properties, and relationships (trace, verify, satisfy, refine) to UAF architectural elements.

View Specifications::Requirements::Requirements

Stakeholders: Requirement Engineers, Solution Providers, Systems Engineers, Software Engineers, Systems Architects, Business Architects.

Concerns: provides a central reference for a set of stakeholder needs expressed as requirements, their relationship (via traceability) to more detailed requirements and the solution described by the architecture that will meet those requirements.

Definition: used to represent requirements, their properties, and relationships (trace, verify, satisfy, refine) between each other and to UAF architectural elements.

Recommended Implementation: SysML Requirement Diagram, tabular format, matrix format.




Figure 8:73 - Requirements

Elements

- Refine
- Requirement
- Satisfy
- Trace
- [UAFElement](#)
- Verify

8.1.14 View Specifications::Information

Stakeholders: Data Modelers, Software Engineers, Systems Engineers

Concerns: address the information perspective on operational, service, and resource architectures.

Definition: allows analysis of an architecture’s information and data definition aspect, without consideration of implementation specific issues.

Recommended Implementation: SysML Block Definition Diagram.

View Specifications::Information::Information Model

Stakeholders: Data Modelers, Software Engineers, Systems Engineers

Concerns: address the information perspective on operational, service, and resource architectures.

Definition: allows analysis of an architecture’s information and data definition aspect, without consideration of implementation specific issues.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:74 - Information Model

Elements

- [DataElement](#)
- [DataModel](#)
- [DataRole](#)
- [Implements](#)
- [InformationElement](#)
- [InformationRole](#)
- [OperationalAsset](#)
- [ResourceAsset](#)

8.1.15 View Specifications::Parameters

Stakeholders: Capability owners, Systems Engineers, Solution Providers.

Concerns: identifies measurable properties that can be used to support engineering analysis and environment for the Capabilities

Definition: Shows the measurable properties of something in the physical world and elements and relationships that are involved in defining the environments applicable to capability, operational concept or set of systems.

View Specifications::Parameters::Parameters: Environment

Stakeholders: Capability owners, Systems Engineers, Solution Providers.

Concerns: defines the environment for the capabilities.

Definition: shows the elements and relationships that are involved in defining the environments applicable to capability, operational concept or set of systems.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:75 - Parameters: Environment

Elements

- [ActivityPerformableUnderCondition](#)
- [ActualCondition](#)
- [ActualEnvironment](#)
- [ActualLocation](#)
- [ActualPropertySet](#)
- [ActualResource](#)
- [Asset](#)
- [Condition](#)
- [Environment](#)
- [EnvironmentProperty](#)
- [GeoPoliticalExtentType](#)
- [Location](#)
- [LocationHolder](#)
- [OperationalRole](#)
- [Process](#)
- [ResourcePerformer](#)
- [ResourceRole](#)

View Specifications::Parameters::Parameters: Measurements

Stakeholders: Capability owners, Systems Engineers, Solution Providers.

Concerns: identifies measurable properties that can be used to support analysis such as KPIs, MoEs, TPIs etc.

Definition: Shows the measurable properties of something in the physical world, expressed in amounts of a unit of measure that can be associated with any element in the architecture.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:76 - Parameters: Measurements

Elements

- [ActualMeasurement](#)
- [ActualMeasurementSet](#)
- [ActualPropertySet](#)
- [ActualService](#)
- [ActualState](#)
- [Capability](#)
- [Competence](#)
- [Condition](#)
- [EnterprisePhase](#)
- [MeasurableElement](#)
- [Measurement](#)
- [MeasurementSet](#)
- [PropertySet](#)
- [ProvidedServiceLevel](#)
- [RequiredServiceLevel](#)
- [Resource](#)
- [ServiceInterface](#)
- [ServiceSpecification](#)

8.1.16 View Specifications::Other

Contains the diagrams that document the use of BPMN, NIEM, IEPPV in the context of UAF.

View Specifications::Other::BPMN

Stakeholders: Business Architects, Enterprise Architects

Concerns: captures activity based behavior and flows.

Definition: describes the activities that are normally conducted in the course of achieving business goals that support a capability. It describes operational activities, their Inputs/Outputs, operational activity actions and flows between them using BPMN.

Recommended Implementation: BPMN Process Diagram.




Figure 8:77 - BPMN

Elements

- [AssetRole](#)
- BPMN2Metamodel::BPMNMessage
- BPMN2Metamodel::CallActivity
- BPMN2Metamodel::MessageFlow
- BPMN2Metamodel::Process
- BPMN2Metamodel::ResourceRole
- BPMN2Metamodel::SequenceFlow
- [Exchange](#)

- [ExchangeItem](#)
- [InteractionMessage](#)
- [InteractionRole](#)
- [InteractionScenario](#)
- [Process](#)
- [ProcessEdge](#)
- [ProcessUsage](#)

View Specifications::Other::IEPPV

Stakeholders: Data Modelers, Solution Providers, Systems Engineers, Software Engineers, Systems Architects, Business Architects, information architects.

Concerns: information exchanges, information interfaces, information interoperability, information sharing and safeguarding.

Definition: UAFP supports information modeling and traceability to IEPPV model elements using the IEPPV-defined elements: Message, SemanticElement, and FilteredSemanticElement, used to represent data, properties/attributes, structure, format, and relationships. The IEPPV profile enables the specification of the policies, rules and constraints governing the packaging (assembly, transformation, marking, redaction) of data elements conforming to information sharing and safeguarding requirements. The IEPPV profile also governs the processing (parsing, transformation, and marshalling) received information and data element.

Recommended Implementation: UML Class Diagram, SysML Block Diagram.




Figure 8:78 - IEPPV

Elements

- Abstraction
- FilteredSemanticElement
- [InformationElement](#)
- InformationSpecification
- Message
- [OperationalExchange](#)
- [OperationalExchangeItem](#)

View Specifications::Other::NIEM

Stakeholders: Data Modelers, Solution Providers, Systems Engineers, Software Engineers, Systems Architects, Business Architects.

Concerns: information exchanges, information interoperability, data schema.

Definition: A specification representing the structure, semantics, and relationships of data objects that satisfy an information exchange requirement. Used for organizing and packaging Model Package Descriptions (MPDs) and Information Exchange Package Documentation (IEPD) as defined by the National Information Exchange Model (NIEM). An IEPD is a type of MPD. The NIEM MPD defines an Enterprise Information Exchange Model (EIEM) as an MPD that contains NIEM-conforming schemas that define and declare data components to be consistently reused in the IEPDs of an enterprise. An EIEM is a collection of schemas organized into a collection of subset schemas and one or more extension schemas. An information sharing enterprise creates and maintains an EIEM.

Recommended Implementation: UML Class Diagram, SysML Block Diagram.




Figure 8:79 - NIEM

Elements

- Abstraction
- [DataElement](#)
- [DataModel](#)
- DataObject
- [InformationElement](#)
- InformationModel

This page intentionally left blank.

9 Domain Metamodel (DMM) Elements

9.1 Domain MetaModel

This package contains the elements of the DMM.

9.1.1 Domain MetaModel::Metadata

Stakeholders: Enterprise Architects, people who want to discover the architecture, Technical Managers.

Concerns: Captures meta-data relevant to the entire architecture

Definition: Provide information pertinent to the entire architecture. Present supporting information rather than architectural models.

Domain MetaModel::Metadata::Taxonomy

ArchitectureMetadata

Package: Taxonomy

isAbstract: No

Generalization: [Metadata](#)

Description

Information associated with an ArchitecturalDescription, that supplements the standard set of tags used to summarize the Architecture. It states things like what methodology was used, notation, etc.




Figure 9:1 - ArchitectureMetadata

InteractionScenarioGeneralization

Package: Taxonomy

isAbstract: No

Generalization: UML2.5Metamodel::Generalization, [MeasurableElement](#)

Description

An InteractionScenarioGeneralization is a taxonomic relationship between a more general InteractionScenario and a more specific InteractionScenario.




Figure 9:2 - InteractionScenarioGeneralization

Metadata

Package: Taxonomy

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A comment that can be applied to any element in the architecture. The attributes associated with this element details the relationship between the element and its related dublinCoreElement, metaDataScheme, category and name. This allows the element to be referenced using the Semantic Web.




Figure 9:3 - Metadata

Attributes

- category : String[0..1] Defines the category of a Metadata element example: <http://purl.org/dc/terms/abstract>.
- dublinCoreTag : String[0..1] A metadata category that is a DublinCore tag.
- metaDataScheme : String[0..1] A representation scheme that defines a set of Metadata.
- name : String[0..1] The name of the Metadata.

ProcessGeneralization

Package: Taxonomy

isAbstract: No

Generalization: UML2.5Metamodel::Generalization, [MeasurableElement](#)

Description

A ProcessGeneralization is a taxonomic relationship between a more general Process and a more specific Process.




Figure 9:4 - ProcessGeneralization

PropertySetGeneralization

Package: Taxonomy

isAbstract: No

Generalization: UML2.5Metamodel::Generalization, [MeasurableElement](#)

Description

A PropertySetGeneralization is a taxonomic relationship between a more general PropertySet and a more specific PropertySet.




Figure 9:5 - PropertySetGeneralization

StateDescriptionGeneralization

Package: Taxonomy

isAbstract: No

Generalization: UML2.5Metamodel::Generalization, [MeasurableElement](#)

Description

A StateDescriptionGeneralization is a taxonomic relationship between a more general StateDescription and a more specific StateDescription.




Figure 9:6 - StateDescriptionGeneralization

Domain MetaModel::Metadata::Structure

EnvironmentProperty

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A property of an Environment that is typed by a Condition. The kinds of Condition that can be represented are Location, GeoPoliticalExtentType and Environment.




Figure 9:7 - EnvironmentProperty

Domain MetaModel::Metadata::Connectivity

Exchange

Package: Connectivity

isAbstract: Yes

Generalization: [MeasurableElement](#), BPMN2Metamodel::MessageFlow, [SubjectOfSecurityConstraint](#)

Description

Abstract tuple, grouping OperationalExchanges and ResourceExchanges that exchange Resources.




Figure 9:8 - Exchange

Exchangeltem

Package: Connectivity

isAbstract: Yes

Generalization: BPMN2Metamodel::BPMNMessage

Description

An abstract grouping for elements that defines the types of elements that can be exchanged between Assets and conveyed by an Exchange.




Figure 9:9 - Exchangeltem

Resource

Package: Connectivity

isAbstract: Yes

Generalization: [PropertySet](#)

Description

Abstract type grouping all elements that can be conveyed by an Exchange.




Figure 9:10 - Resource

Domain MetaModel::Metadata::Processes

ActivityPerformableUnderCondition

Package: Processes

isAbstract: No

Generalization: [MeasurableElement](#)

Description

The ActualCondition under which an Activity is performed.




Figure 9:11 - ActivityPerformableUnderCondition

IsCapableToPerform

Package: Processes

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple defining the traceability between the structural elements to the Activities that they can perform.




Figure 9:12 - IsCapableToPerform

PerformsInContext

Package: Processes

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that relates an OperationalAction to an OperationalRole, or a FunctionAction to a ResourceRole. It indicates that the action can be carried out by the role when used in a specific context or configuration.




Figure 9:13 - PerformsInContext

Process

Package: Processes

isAbstract: Yes

Generalization: [MeasurableElement](#), UML2.5Metamodel::Activity, BPMN2Metamodel::Process

Description

An abstract type that represents a behavior or process (i.e., a Function or OperationalActivity) that can be performed by a Performer.




Figure 9:14 - Process




Figure 9:15 - Process

ProcessEdge

Package: Processes

isAbstract: Yes

Generalization: [MeasurableElement](#), [UML2.5Metamodel::Activity](#), [UML2.5Metamodel::ActivityEdge](#), [BPMN2Metamodel::SequenceFlow](#)

Description

An abstract type that represents a behavior or process (i.e., a [Function](#) or [OperationalActivity](#)) that can be performed by a Performer.




Figure 9:16 - ProcessEdge

ProcessOperation

Package: Processes

isAbstract: Yes

Generalization: [MeasurableElement](#), UML2.5Metamodel::Activity, UML2.5Metamodel::Operation

Description

An abstract type that represents a behavior or process (i.e., a Function or OperationalActivity) that can be performed by a Performer.




Figure 9:17 - ProcessOperation

ProcessParameter

Package: Processes

isAbstract: Yes

Generalization: [MeasurableElement](#), UML2.5Metamodel::Activity, UML2.5Metamodel::CallBehaviorAction, UML2.5Metamodel::Parameter

Description

An abstract type that represents a behavior or process (i.e., a Function or OperationalActivity) that can be performed by a Performer.




Figure 9:18 - ProcessParameter

ProcessUsage

Package: Processes

isAbstract: Yes

Generalization: [MeasurableElement](#), UML2.5Metamodel::Activity, UML2.5Metamodel::CallBehaviorAction, BPMN2Metamodel::CallActivity

Description

An abstract type that represents a behavior or process (i.e., a Function or OperationalActivity) that can be performed by a Performer.




Figure 9:19 - ProcessUsage

Domain MetaModel::Metadata::States

StateDescription

Package: States

isAbstract: Yes

Generalization: UML2.5Metamodel::StateMachine

Description

An abstract type that represents a state machine (i.e., an OperationalStateDescription or ResourceStateDescription), depicting how the Asset responds to various events and the actions.




Figure 9:20 - StateDescription

Domain MetaModel::Metadata::Interaction Scenarios

InteractionMessage

Package: Interaction Scenarios

isAbstract: Yes

Generalization: [MeasurableElement](#), UML2.5Metamodel::Activity, BPMN2Metamodel::Process, UML2.5Metamodel::Interaction, UML2.5Metamodel::Message

Description

An abstract type that groups several types of messages used in the InteractionScenario.

InteractionRole

Package: Interaction Scenarios

isAbstract: Yes

Generalization: BPMN2Metamodel::ResourceRole

Description

An abstract type that represents an individual participant in the InteractionScenario.




Figure 9:21 - InteractionRole

InteractionScenario

Package: Interaction Scenarios

isAbstract: Yes

Generalization: [MeasurableElement](#), UML2.5Metamodel::Activity, BPMN2Metamodel::Process, UML2.5Metamodel::Interaction

Description

An abstract type that specifies interactions between Assets, like ResourcePerformers, and ServiceSpecifications.




Figure 9:22 - InteractionScenario

Domain MetaModel::Metadata::Information

Information

Package: Information

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A comment that describes the state of an item of interest in any medium or form -- and is communicated or received.




Figure 9:23 - Information

Domain MetaModel::Metadata::Constraints

Rule

Package: Constraints

isAbstract: Yes

Generalization: [MeasurableElement](#)

Description

An abstract type for all types of constraint (i.e., an OperationalConstraint could detail the rules of accountancy best practice).




Figure 9:24 - Rule

Domain MetaModel::Metadata::Traceability

ArchitecturalReference

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that specifies that one architectural description refers to another.




Figure 9:25 - ArchitecturalReference

Implements

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that defines how an element in the upper layer of abstraction is implemented by a semantically equivalent element (for example tracing the Functions to the OperationalActivities) in the lower level of abstraction.




Figure 9:26 - Implements

9.1.2 Domain MetaModel::Strategic

Domain MetaModel::Strategic::Taxonomy

Capability

Package: Taxonomy

isAbstract: No

Generalization: [PropertySet](#), [Desirer](#)

Description

A high-level specification of the enterprise's ability to execute a specified course of action.




Figure 9:27 - Capability

CapabilityGeneralization

Package: Taxonomy

isAbstract: No

Generalization: [PropertySetGeneralization](#)

Description

A CapabilityGeneralization is a taxonomic relationship between a more general Capability and a more specific Capability.



Figure 9:28 - CapabilityGeneralization

Domain MetaModel::Strategic::Structure

ActualEnduringTask

Package: Structure

isAbstract: No

Generalization: [CapableElement](#), [ActualPropertySet](#)

Description

An actual undertaking recognized by an enterprise as being essential to achieving its goals - i.e., a strategic specification of what the enterprise does.




Figure 9:29 - ActualEnduringTask

ActualEnterprisePhase

Package: Structure

isAbstract: No

Generalization: [CapableElement](#), [ActualPropertySet](#), [Achiever](#)

Description

An individual that describes the phase of an actual enterprise endeavor.




Figure 9:30 - ActualEnterprisePhase

CapabilityRole

Package: Structure

isAbstract: No

Generalization: [PropertySet](#), [Desirer](#), [MeasurableElement](#)

Description

A high-level specification of the enterprise's ability to execute a specified course of action.




Figure 9:31 - CapabilityRole

EnduringTask

Package: Structure

isAbstract: No

Generalization: [PropertySet](#)

Description

A type of template behavior recognized by an enterprise as being essential to achieving its goals - i.e., a template for a strategic specification of what the enterprise does.




Figure 9:32 - EnduringTask

EnterpriseGoal

Package: Structure

isAbstract: No

Generalization: [PropertySet](#)

Description

A statement about a state or condition of the enterprise to be brought about or sustained through appropriate Means. An EnterpriseGoal amplifies an EnterpriseVision that is, it indicates what must be satisfied on a continuing basis to effectively attain the EnterpriseVision. BMM: OMG dtc-13-08-24.




Figure 9:33 - EnterpriseGoal

Attributes

benefits : String[0..*] A description of the usefulness of the Goal in terms of why the state or condition of the Enterprise is worth attaining.

EnterprisePhase

Package: Structure

isAbstract: No

Generalization: [PropertySet](#)

Description

A type of a current or future state of the enterprise.




Figure 9:34 - EnterprisePhase

EnterpriseVision

Package: Structure

isAbstract: No

Generalization: [PropertySet](#)

Description

A Vision describes the future state of the enterprise, without regard to how it is to be achieved. BMM: OMG dtc-13-08-24.




Figure 9:35 - EnterpriseVision

StructuralPart

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A current or future state of the wholeLifeEnterprise or another EnterprisePhase.




Figure 9:36 - StructuralPart

TemporalPart

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A current or future state of the wholeLifeEnterprise or another EnterprisePhase.




Figure 9:37 - TemporalPart

VisionStatement

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A type of comment that describes the future state of the enterprise, without regard to how it is to be achieved. BMM: OMG dtc-13-08-24.




Figure 9:38 - VisionStatement

WholeLifeEnterprise

Package: Structure

isAbstract: No

Generalization: [EnterprisePhase](#)

Description

A WholeLifeEnterprise is a purposeful endeavor of any size involving people, organizations and supporting systems. It is made up of TemporalParts and StructuralParts.




Figure 9:39 - WholeLifeEnterprise

Domain MetaModel::Strategic::Connectivity

CapabilityDependency

Package: Connectivity

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that one CapabilityDependency is dependent from another.




Figure 9:40 - CapabilityDependency

CapabilityRoleDependency

Package: Connectivity

isAbstract: No

Generalization: [MeasurableElement](#)




Figure 9:41 - CapabilityRoleDependency

Domain MetaModel::Strategic::States

AchievedEffect

Package: States

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that exists between an ActualState (e.g., observed/measured during testing) of an element that attempts to achieve a DesiredEffect and an Achiever.




Figure 9:42 - AchievedEffect

Achiever

Package: States

isAbstract: Yes

Generalization: [UAFEElement](#)

Description

An ActualResource, ActualProject or ActualEnterprisePhase that can deliver a DesiredEffect.




Figure 9:43 - Achiever

DesiredEffect

Package: States

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple relating the Desirer (a Capability or OrganizationalResource) to an ActualState.




Figure 9:44 - DesiredEffect

Desirer

Package: States

isAbstract: Yes

Generalization: [UAFElement](#)

Description

Abstract type used to group architecture elements that might desire a particular effect.




Figure 9:45 - Desirer

Domain MetaModel::Strategic::Traceability

CapabilityForTask

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that a Capability is required in order for an Enterprise to conduct a phase of an EnduringTask.




Figure 9:46 - CapabilityForTask

CapableElement

Package: Traceability

isAbstract: Yes

Generalization: [UAFElement](#)

Description

An abstract type that represents a structural element that can exhibit capabilities.




Figure 9:47 - CapableElement

Exhibits

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that exists between a CapableElement and a Capability that it meets under specific environmental conditions.




Figure 9:48 - Exhibits

MapsToCapability

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple denoting that an Activity contributes to providing a Capability.




Figure 9:49 - MapsToCapability

OrganizationInEnterprise

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple relating an ActualOrganization to an ActualEnterprisePhase to denote that the ActualOrganization plays a role or is a stakeholder in an ActualEnterprisePhase.




Figure 9:50 - OrganizationInEnterprise

9.1.3 Domain MetaModel::Operational

Domain MetaModel::Operational::Taxonomy

ArbitraryConnector

Package: Taxonomy

isAbstract: No

Generalization: [MeasurableElement](#)

Description

Represents a visual indication of a connection used in high level operational concept diagrams.




Figure 9:51 - ArbitraryConnector

ConceptItem

Package: Taxonomy

isAbstract: Yes

Generalization: [UAFElement](#)

Description

Abstract, an item which may feature in a HighLevelOperationalConcept.




Figure 9:52 – ConceptItem

HighLevelOperationalConcept

Package: Taxonomy

isAbstract: No

Generalization: [PropertySet](#)

Description

Describes the Resources and Locations required to meet an operational scenario from an integrated systems point of view. It is used to communicate overall quantitative and qualitative system characteristics to stakeholders.




Figure 9:53 - HighLevelOperationalConcept

Domain MetaModel::Operational::Structure

KnownResource

Package: Structure

isAbstract: No

Generalization: [OperationalPerformer](#), [ResourcePerformer](#)

Description

Asserts that a known ResourcePerformer constrains the implementation of the OperationalPerformer that plays the role in the OperationalArchitecture.




Figure 9:54 - KnownResource

OperationalAgent

Package: Structure

isAbstract: Yes

Generalization: [SubjectOfOperationalConstraint](#), [CapableElement](#), [OperationalAsset](#), [Desirer](#)

Description

An abstract type grouping OperationalArchitecture and OperationalPerformer.




Figure 9:55 - OperationalAgent

OperationalArchitecture

Package: Structure

isAbstract: No

Generalization: [OperationalAgent](#), [Architecture](#)

Description

A type used to denote a model of the Architecture, described from the Operational perspective.




Figure 9:56 - OperationalArchitecture

OperationalMethod

Package: Structure

isAbstract: No

Generalization: [ProcessOperation](#)

Description

A behavioral feature of an OperationalAgent whose behavior is specified in an OperationalActivity.




Figure 9:57 - OperationalMethod

OperationalParameter

Package: Structure

isAbstract: No

Generalization: [ProcessParameter](#)

Description

A type that represents inputs and outputs of an OperationalActivity. It is typed by an OperationalExchangeItem.




Figure 9:58 - OperationalParameter

OperationalPerformer

Package: Structure

isAbstract: No

Generalization: [OperationalAgent](#)

Description

A logical entity that IsCapableToPerform OperationalActivities which produce, consume and process Resources.




Figure 9:59 - OperationalPerformer

OperationalRole

Package: Structure

isAbstract: No

Generalization: [LocationHolder](#), [AssetRole](#), [InteractionRole](#)

Description

Usage of an OperationalPerformer or OperationalArchitecture in the context of another OperationalPerformer or OperationalArchitecture. Creates a whole-part relationship.




Figure 9:60 - OperationalRole

ProblemDomain

Package: Structure

isAbstract: No

Generalization: [OperationalRole](#)

Description

A property associated with an OperationalArchitecture, used to specify the scope of the problem.




Figure 9:61 - ProblemDomain

Domain MetaModel::Operational::Connectivity

OperationalConnector

Package: Connectivity

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A Connector that goes between OperationalRoles representing a need to exchange Resources. It can carry a number of OperationalExchanges.




Figure 9:62 - OperationalConnector

OperationalExchange

Package: Connectivity

isAbstract: No

Generalization: [Exchange](#), [SubjectOfOperationalConstraint](#)

Description

Asserts that a flow can exist between OperationalPerformers (i.e., flows of information, people, materiel, or energy).




Figure 9:63 - OperationalExchange

Attributes

trustLevel : Real[0..1] Captures the directional arbitrary level of trust related to an OperationalExchange between two OperationalPerformers.

OperationalExchangeItem

Package: Connectivity

isAbstract: Yes

Generalization: [Resource](#), [SubjectOfSecurityConstraint](#), [ExchangeItem](#)

Description

An abstract grouping for elements that defines the types of elements that can be exchanged between OperationalPerformers and conveyed by an OperationalExchange.




Figure 9:64 - OperationalExchangeItem

OperationalInterface

Package: Connectivity

isAbstract: No

Generalization: [PropertySet](#)

Description

A declaration that specifies a contract between the OperationalPerformer it is related to, and any other OperationalPerformers it can interact with.




Figure 9:65 - OperationalInterface

OperationalPort

Package: Connectivity

isAbstract: No

Generalization: [MeasurableElement](#)

Description

An interaction point for an OperationalAgent through which it can interact with the outside environment and which is defined by an OperationalInterface.




Figure 9:66 - OperationalPort

OperationalSignal

Package: Connectivity

isAbstract: No

Generalization: [SubjectOfOperationalConstraint](#), [OperationalExchangeItem](#)

Description

An item of information that flows between OperationalPerformers and is produced and consumed by the OperationalActivities that the OperationalPerformers are capable of performing (see IsCapableToPerform).




Figure 9:67 - OperationalSignal

Domain MetaModel::Operational::Processes

OperationalActivity

Package: Processes

isAbstract: No

Generalization: [SubjectOfOperationalConstraint](#), [Process](#)

Description

An Activity that captures a logical process, specified independently of how the process is carried out.




Figure 9:68 - OperationalActivity

OperationalActivityAction

Package: Processes

isAbstract: No

Generalization: [ProcessUsage](#)

Description

A call of an OperationalActivity in the context of another OperationalActivity.




Figure 9:69 - OperationalActivityAction

OperationalActivityEdge

Package: Processes

isAbstract: Yes

Generalization: [ProcessEdge](#)

Description

A tuple that shows the flow of Resources (objects/information) between OperationalActivityActions.




Figure 9:70 - OperationalActivityEdge

StandardOperationalActivity

Package: Processes

isAbstract: No

Generalization: [OperationalActivity](#)

Description

A sub-type of OperationalActivity that is a standard operating procedure.




Figure 9:71 - StandardOperationalActivity

Domain MetaModel::Operational::States

OperationalStateDescription

Package: States

isAbstract: No

Generalization: [MeasurableElement](#), [StateDescription](#)

Description

A state machine describing the behavior of an OperationalPerformer, depicting how the OperationalPerformer responds to various events and the actions.




Figure 9:72 - OperationalStateDescription

Domain MetaModel::Operational::Interaction Scenarios

OperationalInteractionScenario

Package: Interaction Scenarios

isAbstract: No

Generalization: [InteractionScenario](#)

Description

A specification of the interactions between OperationalPerformers in an OperationalArchitecture.




Figure 9:73 - OperationalInteractionScenario

OperationalMessage

Package: Interaction Scenarios

isAbstract: No

Generalization: [InteractionMessage](#)

Description

Message for use in an OperationalInteractionScenario which carries any of the subtypes of OperationalExchange.




Figure 9:74 - OperationalMessage

Domain MetaModel::Operational::Information

InformationElement

Package: Information

isAbstract: No

Generalization: [SubjectOfOperationalConstraint](#), [OperationalAsset](#), [OperationalExchangeItem](#)

Description

An item of information that flows between OperationalPerformers and is produced and consumed by the OperationalActivities that the OperationalPerformers are capable to perform (see IsCapableToPerform).




Figure 9:75 - InformationElement

Domain MetaModel::Operational::Constraints

OperationalConstraint

Package: Constraints

isAbstract: No

Generalization: [Rule](#)

Description

A Rule governing an operational architecture element, i.e., OperationalPerformer, OperationalActivity, InformationElement etc.




Figure 9:76 - OperationalConstraint

SubjectOfOperationalConstraint

Package: Constraints

isAbstract: Yes

Generalization: [UAFElement](#)

Description

An abstract type grouping element that can be the subject of an OperationalConstraint.




Figure 9:77 - SubjectOfOperationalConstraint

9.1.4 Domain MetaModel::Services

Stakeholders: Enterprise Architects, Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: specifications of services required to exhibit a Capability.

Definition: shows Service Specifications and required and provided service levels of these specifications required to exhibit a Capability or to support an Operational Activity.

Domain MetaModel::Services::Taxonomy

ServiceSpecification

Package: Taxonomy

isAbstract: No

Generalization: [PropertySet](#), [VersionedElement](#), [CapableElement](#)

Description

The specification of a set of functionalities provided by one element for the use of others.




Figure 9:78 - ServiceSpecification

ServiceSpecificationGeneralization

Package: Taxonomy

isAbstract: No

Generalization: [PropertySetGeneralization](#)

Description

A ServiceSpecificationGeneralization is a taxonomic relationship between a more general ServiceSpecification and a more specific ServiceSpecification.




Figure 9:79 - ServiceSpecificationGeneralization

Domain MetaModel::Services::Structure

ServiceConnector

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A channel for exchange between two ServiceSpecifications. Where one acts as the consumer of the other.




Figure 9:80 - ServiceConnector

ServiceMethod

Package: Structure

isAbstract: No

Generalization: [ProcessOperation](#)

Description

A behavioral feature of a ServiceSpecification whose behavior is specified in a ServiceFunction.




Figure 9:81 - ServiceMethod

ServiceParameter

Package: Structure

isAbstract: No

Generalization: [ProcessParameter](#)

Description

A type that represents inputs and outputs of a ServiceFunction, represents inputs and outputs of a ServiceSpecification.




Figure 9:82 - ServiceParameter

ServiceSpecificationRole

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#), [InteractionRole](#)

Description

A behavioral feature of a ServiceSpecification whose behavior is specified in a ServiceFunction.




Figure 9:83 - ServiceSpecificationRole

Domain MetaModel::Services::Connectivity

ServiceInterface

Package: Connectivity

isAbstract: No

Generalization: [PropertySet](#)

Description

A contract that defines the ServiceMethods and ServiceMessageHandlers that the ServiceSpecification realizes.




Figure 9:84 - ServiceInterface

ServicePort

Package: Connectivity

isAbstract: No

Generalization: [MeasurableElement](#)

Description

An interaction point for a ServiceSpecification through which it can interact with the outside environment and which is defined by a ServiceInterface.




Figure 9:85 - ServicePort

Domain MetaModel::Services::Processes

ServiceFunction

Package: Processes

isAbstract: No

Generalization: [Process](#)

Description

An Activity that describes the abstract behavior of ServiceSpecifications, regardless of the actual implementation.




Figure 9:86 - ServiceFunction

ServiceFunctionAction

Package: Processes

isAbstract: No

Generalization: [ProcessUsage](#)

Description

A call of a ServiceFunction in the context of another ServiceFunction.




Figure 9:87 - ServiceFunctionAction

ServiceFunctionEdge

Package: Processes

isAbstract: Yes

Generalization: [ProcessEdge](#)

Description

A tuple that shows the flow of Resources (objects/information) between OperationalActivityActions.




Figure 9:88 - ServiceFunctionEdge

Domain MetaModel::Services::States

ServiceStateDescription

Package: States

isAbstract: No

Generalization: [MeasurableElement](#), [StateDescription](#)

Description

A state machine describing the behavior of a ServiceSpecification, depicting how the ServiceSpecification responds to various events and the actions.




Figure 9:89 - ServiceStateDescription

Domain MetaModel::Services::Interaction Scenarios

ServiceInteractionScenario

Package: Interaction Scenarios

isAbstract: No

Generalization: [InteractionScenario](#)

Description

A specification of the interactions between ServiceSpecifications.




Figure 9:90 - ServiceInteractionScenario

ServiceMessage

Package: Interaction Scenarios

isAbstract: No

Generalization: [InteractionMessage](#)

Description

Message for use in a Service Event-Trace.




Figure 9:91 - ServiceMessage

Domain MetaModel::Services::Constraints

ServicePolicy

Package: Constraints

isAbstract: No

Generalization: [Rule](#)

Description

A constraint governing the use of one or more ServiceSpecifications.




Figure 9:92 - ServicePolicy

Domain MetaModel::Services::Traceability

Consumes

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that an OperationalActivity make use of a service.




Figure 9:93 - Consumes

9.1.5 Domain MetaModel::Personnel

Stakeholders: Human resources, Solution Providers, PMs.

Concerns: human factors.

Definition: aims to clarify the role of Human Factors (HF) when creating architectures in order to facilitate both Human Factors Integration (HFI) and systems engineering (SE).

Domain MetaModel::Personnel::Taxonomy

Organization

Package: Taxonomy

isAbstract: No

Generalization: [OrganizationalResource](#)

Description

A group of OrganizationalResources (Persons, Posts, Organizations and Responsibilities) associated for a particular purpose.




Figure 9:94 - Organization

OrganizationalResource

Package: Taxonomy

isAbstract: Yes

Generalization: [PhysicalResource](#), [Stakeholder](#)

Description

An abstract type for Organization, Person, Post and Responsibility.




Figure 9:95 - OrganizationalResource

Person

Package: Taxonomy

isAbstract: No

Generalization: [OrganizationalResource](#)

Description

A type of a human being used to define the characteristics that need to be described for ActualPersons (e.g., properties such as address, telephone number, nationality, etc.).




Figure 9:96 - Person

Post

Package: Taxonomy

isAbstract: No

Generalization: [OrganizationalResource](#)

Description

A type of job title or position that a person can fill (e.g., Lawyer, Solution Architect, Machine Operator or Chief Executive Officer).




Figure 9:97 - Post

Responsibility

Package: Taxonomy

isAbstract: No

Generalization: [OrganizationalResource](#)

Description

The type of duty required of a Person or Organization.




Figure 9:98 - Responsibility

Domain MetaModel::Personnel::Structure

PostRole

Package: Structure

isAbstract: No

Generalization: [OrganizationalResource](#), [ResourceRole](#)

Description

A usage of a post in the context of another OrganizationalResource. Creates a whole-part relationship.




Figure 9:99 - PostRole

SubOrganization

Package: Structure

isAbstract: No

Generalization: [OrganizationalResource](#), [ResourceRole](#)

Description

A type of a human being used to define the characteristics that need to be described for ActualPersons (e.g., properties such as address, telephone number, nationality, etc.).




Figure 9:100 - SubOrganization

Domain MetaModel::Personnel::Connectivity

Command

Package: Connectivity

isAbstract: No

Generalization: [ResourceExchange](#)

Description

A type of ResourceExchange that asserts that one OrganizationalResource commands another.




Figure 9:101 - Command

Control

Package: Connectivity

isAbstract: No

Generalization: [ResourceExchange](#)

Description

A type of ResourceExchange that asserts that one PhysicalResource controls another PhysicalResource (i.e., the driver of a vehicle controlling the vehicle speed or direction).




Figure 9:102 - Control

Domain MetaModel::Personnel::Interaction Scenarios

ResourceInteractionScenario

Package: Interaction Scenarios

isAbstract: No

Generalization: [InteractionScenario](#)

Description

A specification of the interactions between ResourcePerformers in a ResourceArchitecture.




Figure 9:103 - ResourceInteractionScenario

Domain MetaModel::Personnel::Constraints

Competence

Package: Constraints

isAbstract: No

Generalization: [PropertySet](#), [SubjectOfForecast](#)

Description

A specific set of abilities defined by knowledge, skills and aptitude.




Figure 9:104 - Competence

CompetenceForRole

Package: Constraints

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple used to associate an organizational role with a specific set of required competencies.




Figure 9:105 - CompetenceForRole

RequiresCompetence

Package: Constraints

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that an ActualOrganizationalResource is required to have a specific set of Competencies.




Figure 9:106 - RequiresCompetence

Domain MetaModel::Personnel::Roadmap

FillsPost

Package: Roadmap

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that an ActualPerson fills an ActualPost.




Figure 9:107 - FillsPost

Attributes

- endDate : ISO8601DateTime[0..1] End date of an ActualPerson filling an ActualPost.
- startDate : ISO8601DateTime[0..1] Start date of an ActualPerson filling an ActualPost.

Domain MetaModel::Personnel::Traceability

CompetenceToConduct

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple used to associate a Function with a specific set of Competencies needed to conduct the Function.




Figure 9:108 - CompetenceToConduct

9.1.6 Domain MetaModel::Resources

Domain MetaModel::Resources::Taxonomy

CapabilityConfiguration

Package: Taxonomy

isAbstract: No

Generalization: [ResourceArchitecture](#)

Description

A composite structure representing the physical and human resources (and their interactions) in an enterprise, assembled to meet a capability.




Figure 9:109 - CapabilityConfiguration

NaturalResource

Package: Taxonomy

isAbstract: No

Generalization: [PhysicalResource](#)

Description

Type of physical resource that occurs in nature such as oil, water, gas or coal.




Figure 9:110 - NaturalResource

PhysicalResource

Package: Taxonomy

isAbstract: Yes

Generalization: [ResourcePerformer](#)

Description

An abstract type defining physical resources (i.e., OrganizationalResource, ResourceArtifact and NaturalResource).




Figure 9:111 - PhysicalResource

ResourceArchitecture

Package: Taxonomy

isAbstract: No

Generalization: [ResourcePerformer](#), [Architecture](#)

Description

A type used to denote a model of the Architecture, described from the ResourcePerformer perspective.




Figure 9:112 - ResourceArchitecture

ResourceArtifact

Package: Taxonomy

isAbstract: No

Generalization: [PhysicalResource](#)

Description

A type of man-made object that contains no human beings (i.e., satellite, radio, petrol, gasoline, etc.).




Figure 9:113 - ResourceArtifact

ResourcePerformer

Package: Taxonomy

isAbstract: Yes

Generalization: [ResourceExchangeItem](#), [SubjectOfResourceConstraint](#), [OperationalExchangeItem](#), [SubjectOfForecast](#), [CapableElement](#), [Desirer](#), [VersionedElement](#), [ResourceAsset](#)

Description

An abstract grouping of elements that can perform Functions.




Figure 9:114 – ResourcePerformer

Attributes

isStandardConfiguration : Boolean[] Indicates if the ResourcePerformer is StandardConfiguration, default=false.

Software

Package: Taxonomy

isAbstract: No

Generalization: [ResourceArtifact](#)

Description

A sub-type of ResourceArtifact that specifies an executable computer program.




Figure 9:115 - Software

System

Package: Taxonomy

isAbstract: No

Generalization: [ResourceArchitecture](#)

Description

An integrated set of elements, subsystems, or assemblies that accomplish a defined objective. These elements include products (hardware, software, firmware), processes, people, information, techniques, facilities, services, and other support elements (INCOSE SE Handbook V4, 2015).




Figure 9:116 - System

Domain MetaModel::Resources::Structure

ResourceMethod

Package: Structure

isAbstract: No

Generalization: [ProcessOperation](#)

Description

A behavioral feature of a ResourcePerformer whose behavior is specified in a Function.




Figure 9:117 - ResourceMethod

ResourceParameter

Package: Structure

isAbstract: No

Generalization: [ProcessParameter](#)

Description

A type that represents inputs and outputs of a Function. It is typed by a ResourceInteractionItem.




Figure 9:118 - ResourceParameter

ResourcePort

Package: Structure

isAbstract: No

Generalization: [ProtocolImplementation](#), [MeasurableElement](#)

Description

An interaction point for a ResourcePerformer through which it can interact with the outside environment and which is defined by a ResourceInterface.




Figure 9:119 - ResourcePort

ResourceRole

Package: Structure

isAbstract: No

Generalization: [SubjectOfResourceConstraint](#), [LocationHolder](#), [AssetRole](#), [InteractionRole](#)

Description

Usage of a ResourcePerformer in the context of another ResourcePerformer. Creates a whole-part relationship.




Figure 9:120 - ResourceRole

Domain MetaModel::Resources::Connectivity

ResourceConnector

Package: Connectivity

isAbstract: No

Generalization: [ProtocolImplementation](#), [MeasurableElement](#)

Description

A channel for exchange between two ResourceRoles.




Figure 9:121 - ResourceConnector

ResourceExchange

Package: Connectivity

isAbstract: No

Generalization: [Exchange](#)

Description

Asserts that a flow can exist between ResourcePerformers (i.e., flows of data, people, material, or energy).




Figure 9:122 - ResourceExchange

ResourceExchangeItem

Package: Connectivity

isAbstract: Yes

Generalization: [Resource](#), [SubjectOfSecurityConstraint](#), [ExchangeItem](#)

Description

An abstract type grouping elements that defines the types of elements that can be exchanged between ResourcePerformers and conveyed by a ResourceExchange.




Figure 9:123 - ResourceExchangeltem

ResourceInterface

Package: Connectivity

isAbstract: No

Generalization: [PropertySet](#)

Description

A declaration that specifies a contract between the ResourcePerformers it is related to and any other ResourcePerformers it can interact with. It is also intended to be an implementation of a specification of an Interface in the Business and/or Service layer.




Figure 9:124 - ResourceInterface

ResourceSignal

Package: Connectivity

isAbstract: No

Generalization: [ResourceExchangeItem](#)

Description

A property of an element representing something in the physical world, expressed in amounts of a unit of measure.




Figure 9:125 - ResourceSignal

Domain MetaModel::Resources::Processes

Function

Package: Processes

isAbstract: No

Generalization: [SubjectOfResourceConstraint](#), [Process](#)

Description

An Activity which is specified in the context to the ResourcePerformer (human or machine) that IsCapableToPerform it.




Figure 9:126 - Function

FunctionAction

Package: Processes

isAbstract: No

Generalization: [ProcessUsage](#)

Description

A call of a Function indicating that the Function is performed by a ResourceRole in a specific context.




Figure 9:127 - FunctionAction

FunctionEdge

Package: Processes

isAbstract: No

Generalization: [ProcessEdge](#)

Description

A tuple that shows the flow of Resources (objects/data) between FunctionActions.




Figure 9:128 - FunctionEdge

Domain MetaModel::Resources::States

ResourceStateDescription

Package: States

isAbstract: No

Generalization: [MeasurableElement](#), [StateDescription](#)

Description

A state machine describing the behavior of a ResourcePerformer, depicting how the ResourcePerformer responds to various events and the actions.




Figure 9:129 - ResourceStateDescription

Domain MetaModel::Resources::Interaction Scenarios

ResourceMessage

Package: Interaction Scenarios

isAbstract: No

Generalization: [InteractionMessage](#)

Description

Message for use in a Resource Event-Trace which carries any of the subtypes of ResourceExchange.




Figure 9:130 - ResourceMessage

Domain MetaModel::Resources::Information

DataElement

Package: Information

isAbstract: No

Generalization: [SubjectOfResourceConstraint](#), [ResourceAsset](#), [ResourceExchangeItem](#)

Description

A formalized representation of data that is managed by or exchanged between resources.




Figure 9:131 - DataElement

DataRole

Package: Information

isAbstract: No

Generalization: [AssetRole](#)

Description

A usage of DataElement that exists in the context of a ResourceAsset. It also allows the representation of the whole-part aggregation of DataElements.




Figure 9:132 - DataRole

Domain MetaModel::Resources::Constraints

ResourceConstraint

Package: Constraints

isAbstract: No

Generalization: [Rule](#)

Description

A rule governing the structural or functional aspects of an implementation.



Figure 9:133 - ResourceConstraint

SubjectOfResourceConstraint

Package: Constraints

isAbstract: Yes

Generalization: [UAFElement](#)

Description

An abstract type grouping elements that can be the subject of a ResourceConstraint.




Figure 9:134 - SubjectOfResourceConstraint

Domain MetaModel::Resources::Roadmap

Forecast

Package: Roadmap

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that specifies a transition from one Asset, Standard, Competence to another future one. It is related to an ActualEnterprisePhase to give it a temporal context.




Figure 9:135 - Forecast

SubjectOfForecast

Package: Roadmap

isAbstract: Yes

Generalization: [UAFElement](#)

Description

An abstract type grouping elements that can be the subject of a Forecast.




Figure 9:136 - SubjectOfForecast

Technology

Package: Roadmap

isAbstract: No

Generalization: [ResourceArtifact](#)

Description

A sub type of ResourceArtifact that indicates a technology domain, i.e., nuclear, mechanical, electronic, mobile telephony etc.




Figure 9:137 - Technology

VersionedElement

Package: Roadmap

isAbstract: Yes

Generalization: [UAFElement](#)

Description

An abstract type grouping ResourcePerformer and ServiceSpecification that allows VersionOfConfiguration to be related to ActualProjectMilestones.




Figure 9:138 - VersionedElement

VersionOfConfiguration

Package: Roadmap

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A property of a WholeLifeConfiguration, used in version control of a VersionedElement. It asserts that a VersionedElement is a version of a WholeLifeConfiguration.




Figure 9:139 - VersionOfConfiguration

VersionSuccession

Package: Roadmap

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple between two VersionOfConfigurations that denotes that one VersionOfConfiguration follows from another.




Figure 9:140 - VersionSuccession

WholeLifeConfiguration

Package: Roadmap

isAbstract: No

Generalization: [PropertySet](#)

Description

A set of VersionedElements.




Figure 9:141 - WholeLifeConfiguration

Domain MetaModel::Resources::Traceability

ProtocolImplementation

Package: Traceability

isAbstract: Yes

Generalization: [UAFElement](#)

Description

An abstract type grouping architectural elements that can implement Protocols.




Figure 9:142 - ProtocollImplementation

9.1.7 Domain MetaModel::Security

Stakeholders: Security Architects, Security Engineers, Systems Engineers, Operational Architects.

Concerns: addresses the security constraints and information assurance attributes that exist on exchanges between resources and OperationalPerformers

Definition: illustrates the security assets, security constraints, security controls, families, and measures required to address specific security concerns.

Domain MetaModel::Security::Taxonomy

Asset

Package: Taxonomy

isAbstract: Yes

Generalization: [SubjectOfForecast](#), [ConceptItem](#), [LocationHolder](#), [PropertySet](#), [SubjectOfSecurityConstraint](#)

Description

Asset as applied to Security views, an abstract type that indicates the types of elements that can be considered as a subject for security analysis.




Figure 9:143 - Asset

OperationalAsset

Package: Taxonomy

isAbstract: Yes

Generalization: [Asset](#)




Figure 9:144 - OperationalAsset

OperationalMitigation

Package: Taxonomy

isAbstract: No

Generalization: [OperationalArchitecture](#)

Description

A set of OperationalPerformers intended to address against specific operational risks.




Figure 9:145 - OperationalMitigation

ResourceAsset

Package: Taxonomy

isAbstract: Yes

Generalization: [Asset](#)




Figure 9:146 - ResourceAsset

ResourceMitigation

Package: Taxonomy

isAbstract: No

Generalization: [ResourceArchitecture](#)

Description

A set of ResourcePerformers intended to address against specific risks.




Figure 9:147 - ResourceMitigation

SecurityEnclave

Package: Taxonomy

isAbstract: No

Generalization: [ResourceArchitecture](#)

Description

Collection of information systems connected by one or more internal networks under the control of a single authority and security policy. The systems may be structured by physical proximity or by function, independent of location.




Figure 9:148 - SecurityEnclave

Domain MetaModel::Security::Structure

AssetRole

Package: Structure

isAbstract: Yes

Generalization: BPMN2Metamodel::ResourceRole, [SubjectOfSecurityConstraint](#), [MeasurableElement](#)

Description

AssetRole as applied to Security views, an abstract element that indicates the type of elements that can be considered as a subject for security analysis in the particular context.




Figure 9:149 - AssetRole

InformationRole

Package: Structure

isAbstract: No

Generalization: [AssetRole](#)

Description

A usage of InformationElement that exists in the context of an OperationalAsset. It also allows the representation of the whole-part aggregation of InformationElements.




Figure 9:150 - InformationRole

Domain MetaModel::Security::Processes

EnhancedSecurityControl

Package: Processes

isAbstract: No

Generalization: [SecurityControl](#)

Description

Statement of security capability to: (i) build in additional but related, functionality to a basic control; and/or (ii) increase the strength of a basic control.




Figure 9:151 - EnhancedSecurityControl

Enhances

Package: Processes

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple relating the EnhancedSecurityControl to a SecurityControl.




Figure 9:152 - Enhances

Protects

Package: Processes

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that a SecurityControl is required to protect an Asset.




Figure 9:153 - Protects

ProtectsInContext

Package: Processes

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that relates a SecurityControlAction to an OperationalRole, or a ResourceRole. It indicates that SecurityControl is required to protect an Asset in a specific context or configuration.




Figure 9:154 - ProtectsInContext

SecurityProcess

Package: Processes

isAbstract: No

Generalization: [OperationalActivity](#), [Function](#), [SubjectOfSecurityConstraint](#)

Description

The security-related procedure that satisfies the security control requirement.




Figure 9:155 - SecurityProcess

SecurityProcessAction

Package: Processes

isAbstract: No

Generalization: [OperationalActivityAction](#), [FunctionAction](#)

Description

A call of a SecurityProcess in the context of another SecurityProcess.




Figure 9:156 - SecurityProcessAction

Domain MetaModel::Security::Constraints

ActualRisk

Package: Constraints

isAbstract: No

Generalization: [ActualPropertySet](#)

Description

An instance of a Risk. A value holder for Risk Measurements.




Figure 9:157 - ActualRisk

Caveat

Package: Constraints

isAbstract: No

Generalization: [SecurityConstraint](#)

Description

A statement that details alternate conditions under which the rule is not valid.




Figure 9:158 - Caveat

Risk

Package: Constraints

isAbstract: No

Generalization: [PropertySet](#)

Description

A statement of the impact of an event on Assets. It represents a constraint on an Asset in terms of adverse effects, with an associated measure. The measure is used to capture the extent to which an entity is threatened by a potential circumstance or event. Risk is typically a function of: (i) the adverse impacts that would arise if the circumstance or event occurs; and (ii) the likelihood of occurrence.




Figure 9:159 - Risk

SecurityAvailability

Package: Constraints

isAbstract: No

Generalization: [SecurityMeasurement](#)

Description

Details the potential impact on organization or individuals if the information is not available to those who need to access it.




Figure 9:160 - SecurityAvailability

SecurityCategory

Package: Constraints

isAbstract: No

Generalization: [MeasurementSet](#)

Description

The security categories that have been determined for each type of information processed, stored, or transmitted by those information systems. The generalized format for expressing the security category (SC) of an information system is:
 SC information system = {(confidentiality, impact), (integrity, impact), (availability, impact)}.




Figure 9:161 - SecurityCategory

SecurityClassification

Package: Constraints

isAbstract: No

Generalization: [SecurityMeasurement](#)

Description

Details a classification for the exchange.



Figure 9:162 - SecurityClassification

SecurityClassificationKind

Package: Constraints

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A type that defines acceptable values for the security category (SC) of an information system, where the acceptable values for potential impact are low, moderate, or high.




Figure 9:163 - SecurityClassificationKind

SecurityConstraint

Package: Constraints

isAbstract: No

Generalization: [Rule](#)

Description

A type of rule that captures a formal statement to define access control policy language.




Figure 9:164 - SecurityConstraint

SecurityControl

Package: Constraints

isAbstract: No

Generalization: [MeasurableElement](#)

Description

The management, operational, and technical control (i.e., safeguard or countermeasure) prescribed for an information system to protect the confidentiality, integrity, and availability of the system and its information [NIST SP 800-53].




Figure 9:165 - SecurityControl

SecurityControlFamily

Package: Constraints

isAbstract: No

Generalization: [SecurityControl](#)

Description

An element that organizes security controls into a family. Each Security Control Family contains security controls related to the general security topic of the family.




Figure 9:166 – SecurityControlFamily

SecurityIntegrity

Package: Constraints

isAbstract: No

Generalization: [SecurityMeasurement](#)

Description

Details the potential impact on organization or individuals due to modification or destruction of information, and includes ensuring information non-repudiation and authenticity.




Figure 9:167 - SecurityIntegrity

SecurityMeasurement

Package: Constraints

isAbstract: Yes

Generalization: [Measurement](#)

Description

An abstract type grouping all types of security measurements (e.g., SecurityIntegrity, SecurityAvailability).




Figure 9:168 - SecurityMeasurement

SubjectOfSecurityConstraint

Package: Constraints

isAbstract: Yes

Generalization: [UAFElement](#)

Description

An abstract type grouping elements that can be the subject of a SecurityConstraint.




Figure 9:169 - SubjectOfSecurityConstraint

Domain MetaModel::Security::Traceability

Affects

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that a Risk is applicable to an Asset.




Figure 9:170 - Affects

AffectsInContext

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that a Risk is applicable to an AssetRole in the specific context or configuration.




Figure 9:171 – AffectsInContext

Mitigates

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple relating a Security Control to a Risk. Mitigation is established to manage risk and could be represented as an overall strategy or through techniques (mitigation configurations) and procedures (SecurityProcesses).




Figure 9:172 - Mitigates

OwensRisk

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple relating a Risk to an organizational resource that is responsible for executing the risk mitigation.




Figure 9:173 - OwensRisk

OwensRiskInContext

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple relating a Risk to an organizational role that is responsible for executing the risk mitigation in the specific context or configuration.




Figure 9:174 - OwnsRiskInContext

9.1.8 Domain MetaModel::Projects

Domain MetaModel::Projects::Taxonomy

Project

Package: Taxonomy

isAbstract: No

Generalization: [OrganizationalResource](#)

Description

A type that describes types of time-limited endeavors that are required to meet one or more Capability needs.




Figure 9:175 - Project

ProjectMilestone

Package: Taxonomy

isAbstract: No

Generalization: [PropertySet](#)

Description

A type of event in a Project by which progress is measured.




Figure 9:176 - ProjectMilestone

Domain MetaModel::Projects::Structure

ActualProjectMilestoneRole

Package: Structure

isAbstract: No

Generalization: [ActualState](#)

Description

An ActualProjectMilestone that is applied to a ProjectMilestoneRole.




Figure 9:177 - ActualProjectMilestoneRole

ProjectMilestoneRole

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#)

Description

The role played by a ProjectMilestone in the context of a Project.




Figure 9:178 - ProjectMilestoneRole

ProjectStatus

Package: Structure

isAbstract: No

Generalization: [ActualState](#)

Description

The status (i.e., level of progress) of a ProjectTheme for an ActualProject at the time of the ActualProjectMilestone.




Figure 9:179 - ProjectStatus

ProjectTheme

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A property of a ProjectMilestone that captures an aspect by which the progress of ActualProjects may be measured.




Figure 9:180 - ProjectTheme

StatusIndicators

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#)

Description

An enumerated type that specifies a status for a ProjectTheme.




Figure 9:181 - StatusIndicators

Domain MetaModel::Projects::Connectivity

MilestoneDependency

Package: Connectivity

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple between two ActualProjectMilestones that denotes one ActualProjectMilestone follows from another.




Figure 9:182 - MilestoneDependency

Domain MetaModel::Projects::Processes

ProjectActivity

Package: Processes

isAbstract: No

Generalization: [Function](#), [Process](#)

Description

An activity carried out during a project.




Figure 9:183 - ProjectActivity

ProjectActivityAction

Package: Processes

isAbstract: No

Generalization: [FunctionAction](#)

Description

The ProjectActivityAction is defined as a call behavior action that invokes the activity that needs to be performed.




Figure 9:184 - ProjectActivityAction

Domain MetaModel::Projects::Interaction Scenarios

ProjectSequence

Package: Interaction Scenarios

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple between two ActualProjects that denotes one ActualProject cannot start before the previous ActualProject is finished.




Figure 9:185 - ProjectSequence

Domain MetaModel::Projects::Roadmap

ActualProject

Package: Roadmap

isAbstract: No

Generalization: [ActualOrganizationalResource](#), [Achiever](#)

Description

A time-limited endeavor to provide a specific set of ActualResources that meet specific Capability needs.




Figure 9:186 – ActualProject

ActualProjectMilestone

Package: Roadmap

isAbstract: No

Generalization: [ActualPropertySet](#)

Description

An event with a start date in an ActualProject from which progress is measured.




Figure 9:187 - ActualProjectMilestone

Constraints

[1] unnamed1 startTime=endTime

Domain MetaModel::Projects::Traceability

ResponsibleFor

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple between an ActualResponsibleResource and an ActualResponsibility or ActualProject. It defines the duties that the ActualResponsibleResource is ResponsibleFor.




Figure 9:188 – ResponsibleFor

9.1.9 Domain MetaModel::Standards

Stakeholders: Solution Providers, Systems Engineers, Software Engineers, Systems Architects, Business Architects.

Concerns: technical and non-technical Standards applicable to the architecture.

Definition: shows the technical, operational, and business Standards applicable to the architecture. Defines the underlying current and expected Standards.

Domain MetaModel::Standards::Taxonomy

Protocol

Package: Taxonomy

isAbstract: No

Generalization: [Standard](#)

Description

A Standard for communication over a network. Protocols may be composite, represented as a ProtocolStack made up of ProtocolLayers.




Figure 9:189 - Protocol

ProtocolStack

Package: Taxonomy

isAbstract: No

Generalization: [Protocol](#)

Description

A sub type of Protocol that contains the ProtocolLayers, defining a complete stack.




Figure 9:190 - ProtocolStack

Standard

Package: Taxonomy

isAbstract: No

Generalization: [SubjectOfForecast](#), [PropertySet](#)

Description

A ratified and peer-reviewed specification that is used to guide or constrain the architecture. A Standard may be applied to any element in the architecture.




Figure 9:191 - Standard

Attributes

mandatedDate : ISO8601DateTime[0..1] The date when this version of the Standard was published.

retiredDate : ISO8601DateTime[0..1] The date when this version of the Standard was retired.

Domain MetaModel::Standards::Structure

ProtocolLayer

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#)

Description

Usage of a Protocol in the context of another Protocol. Creates a whole-part relationship.




Figure 9:192 – ProtocolLayer

9.1.10 Domain MetaModel::Actual Resources

Stakeholders: Solution Providers, Systems Engineers, Business Architects, Human Resources.

Concerns: the analysis.e.g., evaluation of different alternatives, what-if, trade-offs, V&V on the actual resource configurations.

Definition: illustrates the expected or achieved actual resource configurations and actual relationships between them.

Domain MetaModel::Actual Resources::Taxonomy

ActualOrganization

Package: Taxonomy

isAbstract: No

Generalization: [ActualResponsibleResource](#)

Description

An actual formal or informal organizational unit, e.g., "Driving and Vehicle Licensing Agency", "UAF team Alpha".




Figure 9:193 - ActualOrganization

Attributes

- serviceType : String[0..1] Service office code or symbol
- shortName : String[0..1] String providing a simplified means of identifying an ActualOrganization, i.e. SoftWareGroup could use SWG as the shortName.

ActualOrganizationalResource

Package: Taxonomy

isAbstract: Yes

Generalization: [ActualResource](#), [Stakeholder](#)

Description

Abstract element for an ActualOrganization, ActualPerson or ActualPost.




Figure 9:194 - ActualOrganizationalResource

ActualPerson

Package: Taxonomy

isAbstract: No

Generalization: [ActualResponsibleResource](#)

Description

An individual human being.




Figure 9:195 – ActualPerson

ActualPost

Package: Taxonomy

isAbstract: No

Generalization: [ActualResponsibleResource](#)

Description

An actual, specific post, an instance of a Post "type" - e.g., "President of the United States of America." where the Post would be president.




Figure 9:196 - ActualPost

ActualResource

Package: Taxonomy

isAbstract: No

Generalization: [ActualPropertySet](#), [SubjectOfResourceConstraint](#), [Achiever](#), [CapableElement](#)

Description

An individual, fully-realized ResourcePerformer.




Figure 9:197 – ActualResource

ActualResourceRelationship

Package: Taxonomy

isAbstract: No

Generalization: [UAFElement](#)

Description

An actual resource flow existing between ActualResources (i.e., flow of data, people, materiel, or energy).




Figure 9:198 - ActualResourceRelationship

ActualResponsibility

Package: Taxonomy

isAbstract: No

Generalization: [ActualOrganizationalResource](#)

Description

An actual duty required of a Person or Organization.




Figure 9:199 – ActualResponsibility

ActualResponsibleResource

Package: Taxonomy

isAbstract: Yes

Generalization: [ActualOrganizationalResource](#)

Description

An abstract type grouping responsible OrganizationalResources.




Figure 9:200 - ActualResponsibleResource

FieldedCapability

Package: Taxonomy

isAbstract: No

Generalization: [ActualResource](#)

Description

An individual, fully-realized capability.




Figure 9:201 - FieldedCapability

Domain MetaModel::Actual Resources::Constraints

ActualService

Package: Constraints

isAbstract: Yes

Generalization: [ActualMeasurementSet](#), [CapableElement](#)

Description

An individual ServiceSpecification.




Figure 9:202 - ActualService

ProvidedServiceLevel

Package: Constraints

isAbstract: No

Generalization: [ActualService](#)

Description

A sub type of ActualService that details a specific service level delivered by the provider.




Figure 9:203 - ProvidedServiceLevel

ProvidesCompetence

Package: Constraints

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that an ActualOrganizationalResource provides a specific set of Competencies.




Figure 9:204 - ProvidesCompetence

RequiredServiceLevel

Package: Constraints

isAbstract: No

Generalization: [ActualService](#)

Description

A sub type of ActualService that details a specific service level required of the provider.




Figure 9:205 - RequiredServiceLevel

9.1.11 Domain MetaModel::Dictionary

Stakeholders: Architects, users of the architecture, Capability Owners, Systems Engineers, Solution Providers.

Concerns: Definitions for all the elements in the architecture, libraries of environments and measurements.

Definition: Presents all the elements used in an architecture. Can be used specifically to capture:

- a. Elements and relationships that are involved in defining the environments applicable to capability, operational concept or set of systems.
- b. Measurable properties that can be used to support analysis such as KPIs, MoEs, TPIs etc.

Recommended Implementation: Tabular format, SysML Block Definition Diagram.

Alias

Package: Dictionary

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A metamodel Artifact used to define an alternative name for an element.




Figure 9:206 – Alias

Attributes

nameOwner : String[*] Someone or something that uses this alternative name.

Definition

Package: Dictionary

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A comment containing a description of an element in the architecture.




Figure 9:207 - Definition

Attributes

author : String[*] The original or current person (architect) responsible for the Definition.

SameAs

Package: Dictionary

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that two elements refer to the same real-world thing.




Figure 9:208 – SameAs

9.1.12 Domain MetaModel::Summary & Overview

ArchitecturalDescription

Package: Summary & Overview

isAbstract: No

Generalization: [MeasurableElement](#)

Description

An Architecture Description is a work product used to express the Architecture of some System Of Interest.

It provides executive-level summary information about the architecture description in a consistent form to allow quick reference and comparison between architecture descriptions -- It includes assumptions, constraints, and limitations that may affect high-level decisions relating to an architecture-based work program.




Figure 9:209 - ArchitecturalDescription

Attributes

approvalAuthority : String[*]	Someone or something that has the authority to approve the ArchitecturalDescription.
architect : String[*]	Someone responsible for the creation of ArchitecturalDescription.
assumptionAndConstraint : String[*]	Any assumptions, constraints, and limitations contained in the ArchitecturalDescription, including those affecting deployment, communications performance, information assurance environments, etc.
creatingOrganization : String[*]	The organization responsible for creating the ArchitecturalDescription.
dateCompleted : String[0..1]	Date that the ArchitecturalDescription was completed.
methodologyUsed : String[*]	The methodology used in developing the architecture.
purpose : String[*]	Explains the need for the Architecture, what it will demonstrate, the types of analyses that will be applied to it, who is expected to perform the analyses, what decisions are expected to be made on the basis of each form of analysis, who is expected to make those decisions, and what actions are expected to result.

recommendations : String[*]	States the recommendations that have been developed based on the architecture effort. Examples include recommended system implementations, and opportunities for technology insertion.
status : String[*]	Approval status of the architecture.
summaryOfFindings : String[*]	Summarizes the findings that have been developed so far. This may be updated several times during the development of the ArchitecturalDescription.
toBe : Boolean[1]	Indicates whether the ArchitecturalDescription represents an Architecture that exists or will exist in the future.
toolsUsed : String[*]	Identifies any tools used to develop the ArchitecturalDescription as well as file names and formats if appropriate.
version : String[*]	Version number of the architecture.

Architecture

Package: Summary & Overview

isAbstract: Yes

Generalization: [UAFElement](#)
Description

An abstract type that represents a generic architecture. Subtypes are OperationalArchitecture and PhysicalArchitecture.




Figure 9:210 - Architecture

Concern

Package: Summary & Overview

isAbstract: No

Generalization: [PropertySet](#)

Description

Interest in an EnterprisePhase (EnterprisePhase is synonym for System in ISO 42010) relevant to one or more of its stakeholders.




Figure 9:211 - Concern

Stakeholder

Package: Summary & Overview

isAbstract: Yes

Generalization: [UAFElement](#)

Description

Individual, team, organization, or classes thereof, having an interest in an EnterprisePhase [ISO/IEC/IEEE 42010:2011].




Figure 9:212 - Stakeholder

UAFElement

Package: Summary & Overview

isAbstract: Yes

Description

Abstract super type for all of the UAF elements. It provides a way for all of the UAF elements to have a common set of properties.




Figure 9:213 - UAFElement

Attributes

URI : String[0..1] Captures Unique identifier for the element.

View

Package: Summary & Overview

isAbstract: No

Generalization: [PropertySet](#)

Description

An architecture view expresses the architecture of the system-of-interest in accordance with an architecture viewpoint (or simply, viewpoint). [ISO/IEC/IEEE 42010:2011(E)].




Figure 9:214 - View

Viewpoint

Package: Summary & Overview

isAbstract: No

Generalization: [PropertySet](#)

Description

An architecture viewpoint frames (to formulate or construct in a particular style or language) one or more concerns. A concern can be framed by more than one viewpoint. [ISO/IEC/IEEE 42010:2011(E)].




Figure 9:215 - Viewpoint

Attributes

- language : String[*] The languages used to express the Viewpoint.
- method : String[*] The methods employed in the development of the Viewpoint.
- purpose : String[0..1] The purpose of the Viewpoint.

9.1.13 Domain MetaModel::Information

DataModel

Package: Information

isAbstract: No

Generalization: [SubjectOfOperationalConstraint](#), [SubjectOfResourceConstraint](#)

Description

A structural specification of data types, showing relationships between them. The type of data captured in the DataModel is described using the enumeration DataModelKind (Conceptual, Logical and Physical).




Figure 9:216 - DataModel

9.1.14 Domain MetaModel::Parameters

ActualCondition

Package: Parameters

isAbstract: No

Generalization: [ActualPropertySet](#)

Description

An individual describing an actual situation with respect to circumstances under which an OperationalActivity, Function or ServiceFunction can be performed.




Figure 9:217 - ActualCondition

ActualEnvironment

Package: Parameters

isAbstract: No

Generalization: [ActualCondition](#)

Description

An individual that describes the circumstances of an Environment.



Figure 9:218 - ActualEnvironment

ActualLocation

Package: Parameters

isAbstract: No

Generalization: [ActualCondition](#)

Description

An individual that describes a physical location, for example using text to provide an address, Geo-coordinates, etc.




Figure 9:219 - ActualLocation

Attributes

address : String[0..1]	String describing the address of the ActualLocation, i.e. "1600 Pennsylvania avenue", "The White House"
customKind : String[0..1]	String describing a location kind that is not in the LocationKind enumerated list
locationNamedByAddress : Boolean[]	Boolean that indicates if the ActualLocation address is embedded in the ActualLocation name. By default = false.

ActualMeasurement

Package: Parameters

isAbstract: No

Generalization: [ActualState](#)

Description

An actual value that is applied to a Measurement.




Figure 9:220 - ActualMeasurement

ActualMeasurementSet

Package: Parameters

isAbstract: No

Generalization: [ActualPropertySet](#)

Description

A set of ActualMeasurements.




Figure 9:221 - ActualMeasurementSet

ActualPropertySet

Package: Parameters

isAbstract: No

Generalization: [ActualState](#)

Description

A set or collection of Actual properties.




Figure 9:222 - ActualPropertySet

ActualState

Package: Parameters

isAbstract: Yes

Generalization: [UAFElement](#)

Description

Abstract element that applies temporal extent to a set of elements realized as Instance Specifications.




Figure 9:223 - ActualState

Attributes

endDate : ISO8601DateTime[0..1] End time for all individual elements.

startDate : ISO8601DateTime[0..1] Start time for all individual elements.

Condition

Package: Parameters

isAbstract: No

Generalization: [PropertySet](#)

Description

A type that defines the Location, Environment and/or GeoPoliticalExtent.




Figure 9:224 - Condition

Environment

Package: Parameters

isAbstract: No

Generalization: [Condition](#)

Description

A definition of the environmental factors in which something exists or functions. The definition of an Environment element can be further defined using EnvironmentKind.




Figure 9:225 - Environment

GeoPoliticalExtentType

Package: Parameters

isAbstract: No

Generalization: [Condition](#), [OperationalExchangeItem](#), [ResourceExchangeItem](#)

Description

A type of geospatial extent whose boundaries are defined by declaration or agreement by political parties.




Figure 9:226 - GeoPoliticalExtentType

Attributes

customKind : String[] Captures the kind of GeopoliticalExtentType.

ISO8601DateTime

Package: Parameters

isAbstract: No

Generalization: [UAFElement](#)

Description

A date and time specified in the ISO8601 date-time format including timezone designator (TZD): YYYY-MM-DDThh:mm:ssTZD.




Figure 9:227 - ISO8601DateTime

Location

Package: Parameters

isAbstract: No

Generalization: [ConceptItem](#), [Condition](#)

Description

A specification of the generic area in which a LocationHolder is required to be located.




Figure 9:228 - Location

Attributes

customKind : String[0..1] Captures the kind of Location if the LocationTypeKind has been set to "OtherType".

LocationHolder

Package: Parameters

isAbstract: Yes

Generalization: [UAFElement](#)

Description

Abstract type, used to group elements that are allowed to be associated with a Location.




Figure 9:229 - LocationHolder

MeasurableElement

Package: Parameters

isAbstract: Yes

Generalization: [UAFElement](#)

Description

Abstract type, grouping elements that can be measured by applying MeasurementSets to them.




Figure 9:230 - MeasurableElement

Measurement

Package: Parameters

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A property of an element representing something in the physical world, expressed in amounts of a unit of measure.




Figure 9:231 - Measurement

MeasurementSet

Package: Parameters

isAbstract: No

Generalization: [PropertySet](#)

Description

A collection of Measurements.




Figure 9:232 - MeasurementSet

PropertySet

Package: Parameters

isAbstract: Yes

Generalization: [UAFElement](#)

Description

An abstract type grouping architectural elements that can own Measurements.




Figure 9:233 - PropertySet